



GAP PROFESSIONAL PRODUCTS

Safety Data Sheet Showroom Shine

SECTION 1: Identification

1.1 Product identifier

Product name Showroom Shine

Product number 5529

1.3 Recommended use of the chemical and restrictions on use

Wax Extender / Cleaner

1.4 Supplier's details

Name GAP Professional Products
Address 122 Route 105
Keswick Ridge, NB E6L 1B1
Canada

Telephone (506) 363-9708
Fax (506) 363-4241
email info@gapauto.com

1.5 Emergency phone number(s)

For Medical or Transport Emergencies/
Pour les urgences médicales ou de transport
CANUTEC (24 Hours/Heures)
(613) 996-6666

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

GHS classification in accordance with: (CA) WHMIS 2015

- Acute toxicity, inhalation, Cat. 5
- Skin corrosion/irritation, Cat. 3
- Eye damage/irritation, Cat. 2B

Safety Data Sheet

Showroom Shine

2.2 GHS label elements, including precautionary statements

Pictogram



1. Exclamation mark

Signal word

Warning

Hazard statement(s)

H320

Causes eye irritation

Precautionary statement(s)

P264

Wash ... thoroughly after handling.

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P337+P313

If eye irritation persists: Get medical advice/attention.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Component	Concentration
2-Butoxyethanol (CAS no.: 111-76-2; EC no.: 203-905-0; Index no.: 603-014-00-0)	< 3 % (0)
CLASSIFICATIONS: Skin corrosion/irritation, Cat. 2; Serious eye damage/eye irritation, Cat. 2; Acute toxicity, dermal, Cat. 4; Acute toxicity, inhalation, Cat. 4; Acute toxicity, oral, Cat. 4. HAZARDS: H302 - Harmful if swallowed; H312 - Harmful in contact with skin; H315 - Causes skin irritation; H319 - Causes serious eye irritation; H332 - Harmful if inhaled.	

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet, and get medical attention

In case of skin contact

Immediately flush skin with lots of running water for at least 30 minutes. Remove contaminated clothing and shoes. Wash before reuse.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Safety Data Sheet Showroom Shine

4.2 Most important symptoms/effects, acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

4.3 Indication of immediate medical attention and special treatment needed, if necessary

No data available.

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Not considered a fire hazard.

5.2 Specific hazards arising from the chemical

No specific fire or explosion hazard.

5.3 Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection if necessary. Avoid breathing gas, mist, vapors, spray. Ensure adequate ventilation. Evacuate personnel to safe areas.

For personal protection see section 8.

6.2 Environmental precautions

Do not let concentrated product enter drains.

6.3 Methods and materials for containment and cleaning up

LARGE SPILLS: Dike far ahead of spill to prevent further movement. Recover by pumping or by using a suitable absorbent.
SMALL SPILLS: Contain and absorb with absorbent material and place into containers for later disposal. Wash site of spillage thoroughly with water. Dispose in suitable waste container.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Put on appropriate personal equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Keep in original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container. Wash thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials(see Section 10) and food and drink. Do not store under freezing conditions or above 49 C (120 F). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Keep out of reach from children.

Safety Data Sheet

Showroom Shine

Specific end use(s)

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. 2-Butoxyethanol (CAS: 111-76-2 EC: 203-905-0)

PEL (Inhalation): 50 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 240 mg/m³ (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 20 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 5 ppm (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 20 ppm

97 mg/m³

California permissible exposure limits for chemical contaminants

(Title 8, Article 107)/Skin

TWA (Inhalation): 50 ppm

240 mg/m³; USA (OSHA)

USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants/Skin designation

The value in mg/m³ is approximate

TWA (Inhalation): 5 ppm

24 mg/m³; USA (NIOSH)

USA. NIOSH Recommended Exposure Limits/Potential for dermal absorption

TWA (Inhalation): 20 ppm; USA (ACGIH)

USA. ACGIH Threshold Limit Values (TLV)/Upper Respiratory Tract irritation Eye irritation Substances for which there is a Biological Exposure Index or Indices (see BEI[®] section) Confirmed animal carcinogen with unknown relevance to humans

TLV[®] (Inhalation): 20 ppm; USA (ACGIH)

OSHA Annotated Table Z-1, www.osha.gov

8.2 Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Provide local exhaust or general dilution ventilation to keep exposure to airborne contaminants below the permissible exposure limits where mists or vapors may be generated.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Recommended: Chemical splash goggles Ensure that eyewash stations and/or safety showers are close to the workstation location if working with concentrated product.

Skin protection

Safety Data Sheet

Showroom Shine

Recommended: Chemical-resistant gloves. Neoprene Nitrile

Respiratory protection

Recommended: Dust mask or Respirator should be worn if product is used in confined space or used for a prolonged period of time.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance/form (physical state, color, etc.)	Yellow liquid
Odor	Banana
Odor threshold	N/D
pH	N/A
Melting point/freezing point	N/A
Initial boiling point and boiling range	>212F
Flash point	None
Evaporation rate	1 (water=1)
Flammability (solid, gas)	N/A
Upper/lower flammability limits	LEL=N/A UEL=N/A
Upper/lower explosive limits	N/A
Vapor pressure	N/D
Vapor density	N/D
Relative density	N/D
Solubility(ies)	100%
Partition coefficient: n-octanol/water	N/D
Auto-ignition temperature	N/D
Decomposition temperature	N/D
Viscosity	Thin Liquid
Explosive properties	None
Oxidizing properties	None

SECTION 10: Stability and reactivity

10.1 Reactivity

Contact with incompatible materials.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Stable under normal use conditions.

10.4 Conditions to avoid

None under normal use conditions.

10.5 Incompatible materials

2-Butoxyethanol: Strong oxidizing agents

10.6 Hazardous decomposition products

2-Butoxyethanol: Hazardous decomposition products formed under fire conditions. - Carbon oxides

Safety Data Sheet

Showroom Shine

Other decomposition products - No data available. In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

2-Butoxyethanol LD50 Oral - Rat - 880 mg/kg

2-Butoxyethanol LD50 Skin - Rabbit - 1,060 mg/kg

2-BUTOXYETHANOL LC50 Inhalation - Rat - 450 ppm

2-Butoxyethanol LC50 - Oncorhynchus mykiss (rainbow trout) - 1,474 mg/l - 96 h

2-Butoxyethanol EC50 - Pseudokirchneriella subcapitata (green algae) - 1,840 mg/l - 72 h

ATE (inhalation, gaseous) of mixture: 225000 ppmv

Skin corrosion/irritation

Acute and delayed symptoms and effects:

May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

Serious eye damage/irritation

Acute and delayed symptoms and effects:

Can cause severe irritation, redness, tearing, blurred vision.

Respiratory or skin sensitization

Acute and delayed symptoms and effects:

Breathing of dust or mist can cause mild to severe irritation of nasal or respiratory passage.

Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.

Germ cell mutagenicity

No data available

Carcinogenicity

Carcinogenicity: Ingredients not listed by OSHA, NTP, IARC.

Reproductive toxicity

No data available.

STOT-single exposure

Primary route of entry: A) Skin B) Inhalation

STOT-repeated exposure

Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to product.

Aspiration hazard

May be harmful if swallowed and enters airways.

SECTION 12: Ecological information

Safety Data Sheet

Showroom Shine

Toxicity

ENVIRONMENTAL DATA: No known significant effects or critical hazards

ECOTOXICOLOGICAL INFORMATION: Not Available

SECTION 13: Disposal considerations

Disposal of the product

Dispose of contents/ container in accordance with the local/regional/national/international regulations. Dispose of empty bottle in the trash or recycle where facilities exist.

SECTION 14: Transport information

14.1	UN Number	UN1760
14.2	UN Proper Shipping Name	Sodium Hydroxide
14.3	Transport hazard class(es)	8
14.4	Packing group	2

Special precautions for user

Note: DOT Classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment. Limited Quantity: Small quantities of controlled goods are not regulated as Dangerous Goods according to TDG regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Canadian Domestic Substances List (DSL)

SECTION 16: Other information

16.1 Further information/disclaimer

These SDS are written in an effort to provide information to the worker in the workplace and in such a way it can be understood. To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

16.2 Preparation information

Prepared by Craig Gourley