

acc. to Hazardous Products Regulations (HPR)

Resilience

Version number: GHS 1.0

SECTION 1: Identification

- 1.1 Product identifier
 - Trade name

Resilience - 6616

Vehicle wax

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

1.3 Details of the supplier of the safety data sheet GAP Professional Products 122 Route 205 Keswick Ridge, New Brunswick E6L 1B1

> 1-506-363-9708 www.gapauto.com

1.4 Emergency telephone number

Emergency information service

CANUTEC (24 hours / heures) 1-613-996-6666

Date of compilation: 2018-05-21

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
2.6	flammable liquid	3	Flam. Liq. 3	H226
3.10	aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labeling

H304

- Signal word danger

- Pictograms

GHS02, GHS08



- Hazard statements H226

Flammable liquid and vapour. May be fatal if swallowed and enters airways.

Resilience

Version number: GHS 1.0

Date of compilation: 2018-05-21

- Precautionary staten	nents	
P210	Keep away from heat, hot surfaces, spa	rks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.		
P240	Ground and bond container and receivir	ng equipment.
P241	Use explosion-proof electrical/ventilating	g/lighting equipment.
P242	Use non-sparking tools.	
P243	Take action to prevent static discharges	
P280	Wear protective gloves/protective clothin	ng/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a PC	DISON CENTER/doctor.
P303+P361+P353	IF ON SKIN (or hair): Take off immediat	ely all contaminated clothing. Rinse skin with water or shower.
P331	Do NOT induce vomiting.	
P370+P378	In case of fire: Use sand, carbon dioxide	e or powder extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep co	ol.
P405	Store locked up.	
P501	Dispose of contents/container in accord	ance with local/regional/national/international regulations.
- Hazardous ingredier	nts for labelling	Distillates (petroleum), hydrotreated light

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 **Mixtures**

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
Distillates (petroleum), hydro- treated light	CAS No 64742-47-8	55-<70	Asp. Tox. 1 / H304

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 **Description of first- aid measures**

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Resilience

Version number: GHS 1.0

Date of compilation: 2018-05-21

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

Resilience

Version number: GHS 1.0

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

- Frost
- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

Date of compilation: 2018-05-21

acc. to Hazardous Products Regulations (HPR)

Resilience

Version number: GHS 1.0

Date of compilation: 2018-05-21

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)								
Coun try	Name of agent	CAS No	ldentifi- er	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Source
CA	Jet fuels	64742-47-8	OEL (BC)		200			"BC Regula- tion"
CA	paraffin wax	8002-74-2	OEL (AB)		2			OHS Code
CA	paraffin wax	8002-74-2	OEL (BC)		2			"BC Regula- tion"
CA	paraffin wax	8002-74-2	PEV/VE A		2			Regulation OHS

Notation

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

acc. to Hazardous Products Regulations (HPR)

Resilience

Version number: GHS 1.0

Date of compilation: 2018-05-21

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

liquid light yellow fruity not determined
fruity
not determined
not determined
not determined
>65 °C at 1 atm
44 °C at 101.3 kPa 110 °F at 1 atm
not determined
not relevant, (fluid)
0.6 vol%
4.9 vol%
31.69 hPa at 25 °C
0.88 ^g / _{cm³}
this information is not available
not determined
this information is not available
215 °C
not determined
not explosive (GHS of the United Nations, annex 4)

none

Oxidizing properties

acc. to Hazardous Products Regulations (HPR)

Resilience

Version number: GHS 1.0

Date of compilation: 2018-05-21

9.2 Other information

Temperature class (USA, acc. to NEC 500)

 $T3 \ (\text{maximum permissible surface temperature on the equipment:} \\ \texttt{200°C})$

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Resilience

Version number: GHS 1.0

Date of compilation: 2018-05-21

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Data are not available.

- **12.3 Bioaccumulative potential** Data are not available.
- 12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment Data are not available.

12.6 Other adverse effects

Endocrine disrupting potential

The mixture contains substance(s) with an endocrine disrupting potential.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Resilience

Version number: GHS 1.0 Date of compilation: 2018-05-21 **SECTION 14: Transport information UN number** 14.1 1993 14.2 UN proper shipping name FLAMMABLE LIQUID, N.O.S. 14.3 Transport hazard class(es) Class 3 (flammable liquids) Packing group 14.4 III (substance presenting low danger) 14.5 **Environmental hazards** non-environmentally hazardous acc. to the dangerous goods regulations 14.6 Special precautions for user There is no additional information. 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code The cargo is not intended to be carried in bulk. Information for each of the UN Model Regulations Transport information - National regulations - Additional information (UN RTDG) **UN** number 1993 Proper shipping name FLAMMABLE LIQUID, N.O.S. Class 3 Packing group Ш 3 Danger label(s) Special provisions (SP) 223, 274 (UN RTDG) Excepted quantities (EQ) E1 (UN RTDG) Limited quantities (LQ) 5 L (UN RTDG) International Maritime Dangerous Goods Code (IMDG) **UN** number 1993 Proper shipping name FLAMMABLE LIQUID, N.O.S. Class 3 Marine pollutant Packing group 111 Danger label(s) 3 Special provisions (SP) 223, 274, 955 Excepted quantities (EQ) E1 Limited quantities (LQ) 5 L EmS F-E, S-E

Resilience

on number: GHS 1.0	Date of compilation: 2018-05-2
Stowage category	Α
International Civil Aviation Organiza	tion (ICAO-IATA/DGR)
UN number	1993
Proper shipping name	Flammable liquid, n.o.s.
Class	3
Packing group	III
Danger label(s)	3
•	
Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	0	no significant risk to health
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperat- ures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperat- ures before ignition can occur
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

acc. to Hazardous Products Regulations (HPR)

Resilience

Version number: GHS 1.0

Date of compilation: 2018-05-21

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations			
"BC Regulation"	OHS Regulation: Section 5.48 (British Columbia)			
Asp. Tox.	Aspiration hazard			
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)			
DGR	Dangerous Goods Regulations (see IATA/DGR)			
EmS	Emergency Schedule			
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations			
IATA	International Air Transport Association			
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)			
ICAO	International Civil Aviation Organization			
IMDG	International Maritime Dangerous Goods Code			
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")			
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition			
OHS Code	Occupational Health and Safety Code: Occupational exposure limits for chemical substances (Alberta)			
PBT	Persistent, Bioaccumulative and Toxic			
ppm	Parts per million			
Regulation OHS	Regulation respecting occupational health and safety: Permissible exposure values for airborne contaminants (Quebec)			
STEL	Short-term exposure limit			
TWA	Time-weighted average			
vPvB	Very Persistent and very Bioaccumulative			

Key literature references and sources for data

Hazardous Products Regulations (HPR).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.