

acc. to Hazardous Products Regulations (HPR)

LT Yellow

Version number: GHS 1.0 Date of compilation: 2018-05-21 **SECTION 1: Identification** LT Yellow 1.1 **Product Name** Product Number 6628 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses Vehicle polishing compound 1.3 Details of the supplier of the safety data sheet **GAP** Professional Products 122 Route 205 Keswick Ridge, New Brunswick E6L 1B1 1-506-363-9708 www.gapauto.com 1.4 **Emergency telephone number** Emergency information service CANUTEC (24 hours / heures) 1-613-996-6666

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
2.6	flammable liquid	4	Flam. Liq. 4	H227
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.4S	skin sensitization	1	Skin Sens. 1	H317
3.7	reproductive toxicity	2	Repr. 2	H361f
3.10	aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labeling

- Signal word danger
- Pictograms

GHS07, GHS08



 Hazard statements 	
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H361f	Suspected of damaging fertility.

LT Yellow

Version number: GHS 1.0

Date of compilation: 2018-05-21

- Precautionary sta	atements
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352	IF ON SKIN: Wash with plenty of water.
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403	Store in a well-ventilated place.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
	dianta for labelling

- Hazardous ingredients for labelling

octamethylcyclotetrasiloxane, CMIT/MIT mixture, odorless mineral spirits

2.3 Other hazards

This material is combustible, but will not ignite readily. Special danger of slipping by leaking/spilling product.

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
odorless mineral spirits	CAS No 64742-48-9	3-<12	Flam. Liq. 3 / H226 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304
Distillates (petroleum), hydro- treated light	CAS No 64742-47-8	3-<12	Asp. Tox. 1 / H304
octamethylcyclotetrasiloxane	CAS No 556-67-2	3-<12	Flam. Liq. 3 / H226 Repr. 2 / H361f
CMIT/MIT mixture	CAS No 55965-84-9	0-<0.1	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Skin Sens. 1 / H317

For full text of abbreviations: see SECTION 16.

acc. to Hazardous Products Regulations (HPR)

LT Yellow

Version number: GHS 1.0

SECTION 4: First-aid measures

4.1 Description of first- aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Date of compilation: 2018-05-21

acc. to Hazardous Products Regulations (HPR)

LT Yellow

Version number: GHS 1.0

Date of compilation: 2018-05-21

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

LT Yellow

Version number: GHS 1.0

Date of compilation: 2018-05-21

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

Frost

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occup	Occupational exposure limit values (Workplace Exposure Limits)							
Coun try	Name of agent	CAS No	ldentifi- er	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Source
CA	aluminium, insoluble com- pounds	1344-28-1	OEL (BC)		1			"BC Regula- tion"
CA	aluminium oxide	1344-28-1	PEV/VE A		10			Regulation OHS
CA	Aluminum oxide (Alumina)	1344-28-1	OEL (AB)		10			OHS Code
CA	Jet fuels	64742-47-8	OEL (BC)		200			"BC Regula- tion"

 $\frac{\text{Notation}}{\text{STEL}}$

TWA

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified

Relevant DNELs of components of the mixture							
Name of substance	CAS No	End- point	Threshold level	Protection goal, route of exposure	Used in	Exposure time	
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects	
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects	
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	chronic - local ef- fects	
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	acute - local ef- fects	

acc. to Hazardous Products Regulations (HPR)

LT Yellow

Version number: GHS 1.0

Date of compilation: 2018-05-21

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
octamethylcyclotet- rasiloxane	556-67-2	PNEC	10 ^{mg} / _l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.059 ^{mg} / _{kg}	pelagic organisms	sediments	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	1.7 ^{mg} / _{kg}	(top) predators	water	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.44 ^{µg} / _l	aquatic organisms	freshwater	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.044 ^{µg} / _l	aquatic organisms	marine water	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	10 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	3 ^{mg} / _{kg}	aquatic organisms	freshwater sedi- ment	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.3 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.59 ^{mg} / _{kg}	benthic organisms	sediments	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.16 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

acc. to Hazardous Products Regulations (HPR)

LT Yellow

Version number: GHS 1.0

Date of compilation: 2018-05-21

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	liquid (viscous)
Color	light yellow
Odor	citrus
Other safety parameters	
pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	>65 °C at 1 atm
Flash point	63 °C at 101.3 kPa 146 °F at 1 atm
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Explosive limits	
- Lower explosion limit (LEL)	0.6 vol%
- Upper explosion limit (UEL)	5.4 vol%
Vapor pressure	31.69 hPa at 25 °C
Density	1 – 1.02 ^g / _{cm³} at 25 °C
Vapor density	this information is not available
Solubility(ies)	
- Water solubility	miscible in any proportion
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	215 °C
Viscosity	not determined
Explosive properties	not explosive (GHS of the United Nations, annex 4)
Oxidizing properties	none

acc. to Hazardous Products Regulations (HPR)

LT Yellow

Version number: GHS 1.0

Date of compilation: 2018-05-21

9.2 Other information

Temperature class (USA, acc. to NEC 500)

 $T3 \ (\text{maximum permissible surface temperature on the equipment:} \\ \texttt{200°C})$

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture					
Name of substance	CAS No	Exposure route	ATE		
CMIT/MIT mixture	55965-84-9	oral	100 ^{mg} / _{kg}		
CMIT/MIT mixture	55965-84-9	dermal	300 ^{mg} / _{kg}		
CMIT/MIT mixture	55965-84-9	inhalation: vapour	3 ^{mg} / _l /4h		

LT Yellow

Date of compilation: 2018-05-21

Version number: GHS 1.0

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Suspected of damaging fertility.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Endocrine disrupting potential

The mixture contains substance(s) with an endocrine disrupting potential.

acc. to Hazardous Products Regulations (HPR)

LT Yellow

Version number: GHS 1.0

Date of compilation: 2018-05-21

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

not relevant

none

SECTION 14: Transport information

- 14.1 UN number
- 14.2 UN proper shipping name
- 14.3 Transport hazard class(es)
- 14.4 Packing group
- 14.5 Environmental hazards

not relevant non-environmentally hazardous acc. to the dangerous goods regulations

not subject to transport regulations

14.6 Special precautions for user There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

International Maritime Dangerous Goods Code (IMDG)

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4) none of the ingredients are listed

LT Yellow

Version number: GHS 1.0

Date of compilation: 2018-05-21

Clean Air Act

none of the ingredients are listed

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperat- ures before ignition can occur
Physical hazard	1	material that is normally stable but can become unstable (self-react) at high temperatures and pressures. Material may react non-violently with water or undergo hazardous polymer- ization in the absence of inhibitors
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperat- ures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
"BC Regulation"	OHS Regulation: Section 5.48 (British Columbia)
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)

acc. to Hazardous Products Regulations (HPR)

LT Yellow

Version number: GHS 1.0

Date of compilation: 2018-05-21

Abbr.	Descriptions of used abbreviations
DNEL	Derived No-Effect Level
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
ΙΑΤΑ	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OHS Code	Occupational Health and Safety Code: Occupational exposure limits for chemical substances (Alberta)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Regulation OHS	Regulation respecting occupational health and safety: Permissible exposure values for airborne contaminants (Quebec)
Repr.	Reproductive toxicity
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative
OHS Code PBT PNEC ppm Regulation OHS Repr. Skin Corr. Skin Corr. Skin Sens. Stin Sens. STEL STOT SE TWA	Occupational Health and Safety Code: Occupational exposure limits for chemical substances (Alberta) Persistent, Bioaccumulative and Toxic Predicted No-Effect Concentration Parts per million Regulation respecting occupational health and safety: Permissible exposure values for airborne contaminants (Quebec) Reproductive toxicity Corrosive to skin Irritant to skin Skin sensitization Short-term exposure limit Specific target organ toxicity - single exposure Time-weighted average

Key literature references and sources for data

Hazardous Products Regulations (HPR).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

acc. to Hazardous Products Regulations (HPR)

LT Yellow

Version number: GHS 1.0

Date of compilation: 2018-05-21

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.