



GAP PROFESSIONAL PRODUCTS

Safety Data Sheet 245 Chip Prep

SECTION 1: Identification

1.1 Product identifier

Product name 245 Chip Prep

Product number FLR1103

1.3 Recommended use of the chemical and restrictions on use

Solvent pre-cleaner

1.4 Supplier's details

Name GAP Professional Products
Address 122 Route 105
Keswick Ridge NB E6L 1B1
Canada

Telephone (506) 363-9708
Fax (506) 363-4241
email info@gapauto.com

1.5 Emergency phone number(s)

For Medical or Transport Emergencies / Pour les urgences médicales ou de transport
CANUTEC (24 Hours)
(613) 996-6666

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

GHS classification in accordance with: WHMIS 2015

- Acute toxicity, inhalation, Cat. 4
- Skin corrosion/irritation, Cat. 2
- Flammable liquids, Cat. 3
- Acute toxicity, dermal, Cat. 5

Safety Data Sheet

245 Chip Prep

- Acute toxicity, inhalation, Cat. 5

2.2 GHS label elements, including precautionary statements

Pictogram



1. Exclamation mark; 2. Flame

Signal word

Warning

Hazard statement(s)

H312
H315
H332
H226

Harmful in contact with skin
Causes skin irritation
Harmful if inhaled
Flammable liquid and vapor

Precautionary statement(s)

P261
P264
P271
P280
P302+P352
P304+P340
P312
P321
P332+P313
P362+P364
P501
P210

Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash ... thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/eye protection/face protection/protective clothing.
IF ON SKIN: Wash with plenty of water/...
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor/... if you feel unwell.
Specific treatment (see ... on this label).
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Dispose of contents/container to ...
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
Keep container tightly closed.
Ground and bond container and receiving equipment.
Use explosion-proof [electrical/ventilating/lighting/...] equipment.
Use non-sparking tools.
Take action to prevent static discharges.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
In case of fire: Use ... to extinguish.
Store in a well-ventilated place. Keep cool.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Component	Concentration
XYLENES (MIXED) (CAS no.: 1330-20-7; EC no.: 215-535-7; Index no.: 601-022-00-9)	60 - 100 % (weight)

Safety Data Sheet

245 Chip Prep

CLASSIFICATIONS: Flammable liquids, Cat. 3; Acute toxicity, inhalation, Cat. 4; Acute toxicity, dermal, Cat. 4; Skin corrosion/irritation, Cat. 2. HAZARDS: H226 - Flammable liquid and vapor; H312 - Harmful in contact with skin; H315 - Causes skin irritation; H332 - Harmful if inhaled.

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

General advice	Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet, and get medical attention
In case of skin contact	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician
In case of eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.
If swallowed	DO NOT INDUCE VOMITING. Call physician immediately. If conscious give lots of water or milk. Do not give anything by mouth to an unconscious or convulsing person.
Personal protective equipment for first-aid responders	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Wear personal protective clothing (see section 8).

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Regular foam, waterfog, carbon dioxide or dry chemical. Keep containers cool with water spray using fog nozzles.

5.2 Specific hazards arising from the chemical

Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights and other flames in locations distant from the material handling point.

5.3 Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

See Section 8 for recommended personal protective equipment.

6.2 Environmental precautions

Should not be released into the environment.

6.3 Methods and materials for containment and cleaning up

Safety Data Sheet 245 Chip Prep

Solvents

LARGE SPILLS: Dike far ahead of spill to prevent further movement. Soak up with inert absorbent material (e.g. sand, silica gel). Keep in suitable, closed containers for disposal.

SMALL SPILLS: Contain and absorb with absorbent material and place into containers for later disposal. Dispose of according to local, and Provincial regulations for products containing petroleum distillates.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Put on appropriate personal equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Keep in original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container. Wash thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials(see Section 10) and food and drink. Do not store under freezing conditions or above 49 C (120 F). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Keep out of reach from children.

Specific end use(s)

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. Xylenes (o-, m-, p-isomers) (CAS: 1330-20-7)

PEL (Inhalation): 100 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 435 mg/m³ (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 100 ppm, (ST) 150 ppm, (C) 300 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 100 ppm, (ST) 150 ppm (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

8.2 Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Splash goggles

Skin protection

Chemical resistant gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Wash and dry hands after use.

Safety Data Sheet

245 Chip Prep

Body protection

Skin Protection: Protective gloves (for hands). Long sleeve shirts and pants should be worn to protect exposed skin.

Respiratory protection

Recommended: Dust mask or Respirator should be worn if product is used in confined space or used for a prolonged period of time.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance/form (physical state, color, etc.)	Clear
Odor	Aromatic odour
Odor threshold	
pH	Not Available
Melting point/freezing point	Not Available
Initial boiling point and boiling range	>240° F
Flash point	108° F T.C.C.
Evaporation rate	<1 (l'eau = 1)
Flammability (solid, gas)	product mist may be flammable
Upper/lower flammability limits	LEL=0.9% UEL=6%
Vapor pressure	Not determined
Vapor density	Not Determined
Relative density	Not Determined
Solubility(ies)	Negligible in water.
Partition coefficient: n-octanol/water	Not Determined
Auto-ignition temperature	Not Determined
Decomposition temperature	Not Determined
Viscosity	Thin Liquid
Explosive properties	
Oxidizing properties	

SECTION 10: Stability and reactivity

10.1 Reactivity

None under normal use conditions.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Will not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Avoid contact with acids and strong oxidizers such as permanganate, chlorine, ectoderm. Do not store near acids, carbon dioxide (CO₂), and strong oxidizers such as permanganate, chlorine, ectoderm.

10.6 Hazardous decomposition products

Safety Data Sheet 245 Chip Prep

After water evaporates, burning may produce oxides of carbon, traces of sulfur and nitrogen oxides and various hydrocarbons

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

ATE (inhalation, vapor) of mixture: 22 mg/l

ATE (dermal) of mixture: 2200 mg/kg

ATE (inhalation, gaseous) of mixture: 9000 ppmv

ATE (inhalation, vapor) of mixture: 22 mg/l

ATE (dermal) of mixture: 1100 mg/kg

Skin corrosion/irritation

Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.

Serious eye damage/irritation

Can cause severe irritation, redness, tearing, blurred vision.

Respiratory or skin sensitization

Excessive inhalation of vapors can cause nasal and respiratory irritation and central nervous system effects including dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

Germ cell mutagenicity

No data available

Carcinogenicity

Carcinogenicity: Ingredients not listed by OSHA, NTP, IARC.

Reproductive toxicity

No data available

Summary of evaluation of the CMR properties

Not Available

STOT-single exposure

Primary route of entry: A) Skin B) Inhalation

Not classified as a specific target organ toxicant (single exposure).

STOT-repeated exposure

Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to product.

Additional information

Safety Data Sheet 245 Chip Prep

XYLENES (MIXED): *TOXICITY:

typ. dose mode specie amount unit other

TCLo ihl hmn 200 ppm

LCLo ihl man 10000 ppm/6H

LD50 orl rat 4300 mg/kg

LC50 ihl rat 5000 ppm/4H

LD50 scu rat 1700 mg/kg

LD50 ipr mus 1548 mg/kg

LDLo ipr gpg 2000 mg/kg

LDLo ipr mam 2000 mg/kg

LCLo ihl gpg 450 ppm

LDLo orl hmn 50 mg/kg

*AQTX/TLM96: 100-10 ppm

*SAX TOXICITY EVALUATION:

THR = MODERATE via inhalation and oral routes.

*CARCINOGENICITY:

Review: IARC Cancer Review: Human Inadequate Evidence

IARC Cancer Review: Animal Inadequate Evidence

IARC: Not classifiable as a human carcinogen (Group 3) [610]

Status: NTP Carcinogenesis Studies (Gavage); No Evidence: Male and Female Rat,

Male and Female Mouse [620]

*MUTATION DATA:

test lowest dose | test lowest dose

----- | -----

cyt-smc 1 mmol/tube |

*TERATOGENICITY:

Reproductive Effects Data:

TCLo: ihl-rat 1000 mg/m³/24H (9-14D preg)

TCLo: ihl-rat 50 mg/m³/6H (1-21D preg)

TCLo: ihl-rat 600 mg/m³/24H (7-15D preg)

TDLo: orl-mus 20600 ug/kg (6-15D preg)

TCLo: ihl-mus 4000 ppm/6H (6-12D preg)

TDLo: orl-mus 31 mg/kg (6-15D preg)

TCLo: ihl-mus 2000 ppm/6H (6-12D preg)

*STANDARDS, REGULATIONS & RECOMMENDATIONS:

OSHA: Federal Register (1/19/89) and 29 CFR 1910.1000 Subpart Z

Transitional Limit: PEL-TWA 100 ppm [610]

Final Limit: PEL-TWA 100 ppm; STEL 150 ppm [610]

ACGIH: TLV-TWA 100 ppm; STEL 150 ppm [610]

NIOSH Criteria Document: Recommended Exposure Limit to this compound-air:

TWA 100 ppm; Ceiling Limit 200 ppm/10M [015,610]

NFPA Hazard Rating: Health (H): 2

Flammability (F): 3

Reactivity (R): 0

H2: Materials hazardous to health, but areas may be entered freely with full-faced mask self-contained breathing apparatus which provides eye protection (see NFPA for details).

Safety Data Sheet 245 Chip Prep

F3: Materials which can be ignited under almost all normal temperature conditions (see NFPA for details).

R0: Materials which are normally stable even under fire exposure conditions and which are not reactive with water (see NFPA for details).

*OTHER TOXICITY DATA:

Skin and Eye Irritation Data:

eye-hmn 200 ppm

skn-rbt 100% MOD

skn-rbt 500 mg/24H MOD

eye-rbt 87 mg MLD

eye-rbt 5 mg/24H SEV

Standards and Regulations: DOT-Hazard: Flammable liquid; Label: Flammable liquid

DOT-IMO: Flammable or Combustible liquid; Label: Flammable liquid

Status: NIOSH Analytical Methods: see hydrocarbons, aromatic, 1501

EPA TSCA Chemical Inventory, 1986

EPA TSCA 8(a) Preliminary Assessment Information, Final Rule

EPA Genetox Program 1986, Negative: In vitro SCE-human lymphocytes;

In vitro SCE-human

EPA TSCA Test Submission (TSCATS) Data Base, December 1986

Meets criteria for proposed OSHA Medical Records Rule

SECTION 12: Ecological information

Toxicity

ECOTOXICOLOGICAL INFORMATION: Not Available ENVIRONMENTAL DATA: No known significant effects or critical hazards

ECOTOXICOLOGICAL INFORMATION: Not Available

SECTION 13: Disposal considerations

Disposal of the product

Dispose of accordance in local, and provincial regulations for solvent materials.

SECTION 14: Transport information

14.1	UN Number	1307
14.2	UN Proper Shipping Name	Xylenes
14.3	Transport hazard class(es)	3
14.4	Packing group	3

Special precautions for user

Note: DOT Classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment. Limited Quantity: Small quantities of controlled goods are not regulated as Dangerous Goods according to TDG regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Canadian Domestic Substances List (DSL)

Safety Data Sheet

245 Chip Prep

California Prop. 65 components

Chemical name: XYLENES (MIXED)

CAS number: 1330-20-7

06/11/2004 - Cancer

SECTION 16: Other information

16.1 Further information/disclaimer

These SDS are written in an effort to provide information to the worker in the workplace and in such a way it can be understood. To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

16.2 Preparation information

Prepared by: C. Gourley