



## GAP PROFESSIONAL PRODUCTS

### Safety Data Sheet GAP Brake Cleaner

#### SECTION 1: Identification

##### 1.1 GHS Product identifier

Product name	GAP Brake Cleaner
Product number	88250
Brand	GAP Professional Products

##### 1.3 Recommended use of the chemical and restrictions on use

Brake parts cleaner

##### 1.4 Supplier's details

Name	GAP Professional Products
Address	122 Route 105 Keswick Ridge NB E6L 1B1 Canada
Telephone	(506) 363-9708
Fax	(506) 363-4241
email	info@gapauto.com

##### 1.5 Emergency phone number

For Medical or Transport Emergencies / Pour les urgences médicales ou de transport  
CANUTEC (24 Hours)  
(613) 996-6666

#### SECTION 2: Hazard identification

##### 2.1 Classification of the substance or mixture

###### GHS classification in accordance with: WHMIS 2015

- Acute toxicity, inhalation, Cat. 4
- Skin corrosion/irritation, Cat. 2
- Flammable liquids, Cat. 2
- Aerosols, Cat. 1
- Gases under pressure, compressed gas
- Specific target organ toxicity following single exposure, Cat. 3
- Aspiration hazard, Cat. 1

# Safety Data Sheet

## GAP Brake Cleaner

### 2.2 GHS label elements, including precautionary statements

#### Pictograms



1. Exclamation mark; 2. Flame; 3. Gas cylinder; 4. Health hazard

#### Signal word

**Danger**

#### Hazard statement(s)

H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H229	Pressurized container: may burst if heated
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

#### Precautionary statement(s)

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting/...] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash ... thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
P302+P352	IF ON SKIN: Wash with plenty of water/...
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor/... if you feel unwell.
P321	Specific treatment (see ... on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use ... to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.

# Safety Data Sheet

## GAP Brake Cleaner

P410+P412  
P501

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Dispose of contents/container to ...

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Hazardous components

Component	Concentration
<b>Acetone (CAS no.: 67-64-1; EC no.: 200-662-2; Index no.: 606-001-00-8)</b> CLASSIFICATIONS: Flammable liquids, Cat. 2; Specific target organ toxicity, single exposure, Cat. 3; Eye damage/irritation, Cat. 2. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irritation; H336 - May cause drowsiness or dizziness.	< 50 - < 95 % (weight)
<b>Carbon dioxide (CAS no.: 124-38-9; EC no.: 204-696-9)</b> CLASSIFICATIONS: No data available. HAZARDS: No data available.	5 - 10 % (weight)
<b>Heptane (CAS no.: 142-82-5; EC no.: 205-563-8; Index no.: 601-008-00-2)</b> CLASSIFICATIONS: Flammable liquids, Cat. 2; Aspiration hazard, Cat. 1; Skin corrosion/irritation, Cat. 2; Specific target organ toxicity, single exposure, Cat. 3; Hazardous to the aquatic environment, short-term (acute), Cat. 1; Hazardous to the aquatic environment, long-term (chronic), Cat. 1. HAZARDS: H225 - Highly flammable liquid and vapor; H304 - May be fatal if swallowed and enters airways; H315 - Causes skin irritation; H336 - May cause drowsiness or dizziness; H400 - Very toxic to aquatic life; H410 - Very toxic to aquatic life with long lasting effects.	> 5 - < 10 % (weight)

### SECTION 4: First-aid measures

#### 4.1 Description of necessary first-aid measures

General advice	Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet, and get medical attention
In case of skin contact	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician
In case of eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.
If swallowed	DO NOT INDUCE VOMITING. Call physician immediately. If conscious give lots of water or milk. Do not give anything by mouth to an unconscious or convulsing person.
Personal protective equipment for first-aid responders	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Wear personal protective clothing (see section 8).

### SECTION 5: Fire-fighting measures

#### 5.1 Suitable extinguishing media

Regular foam, waterfog, carbon dioxide or dry chemical. Keep containers cool with water spray using fog nozzles.

#### 5.2 Specific hazards arising from the chemical

## Safety Data Sheet GAP Brake Cleaner

Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights and other flames in locations distant from the material handling point.

### 5.3 Special protective actions for fire-fighters

Extremely flammable liquid and vapour. Can ignite at room temperature. Releases vapour that can form explosive mixture with air. Sprayed product will project a flame on contact with an ignition source. Do not use on vehicles unless cool. Containers may explode if heated. Vapours are heavier than air. May travel a considerable distance to a source of ignition and flash back to a leak or open container.  
Carbon oxides, and other unidentified organic compounds.

#### Further information

Use water spray to cool unopened containers.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

See Section 8 for recommended personal protective equipment.

### 6.2 Environmental precautions

Should not be released into the environment.

### 6.3 Methods and materials for containment and cleaning up

Solvents

LARGE SPILLS: Dike far ahead of spill to prevent further movement. Soak up with inert absorbent material (e.g. sand, silica gel). Keep in suitable, closed containers for disposal.

SMALL SPILLS: Contain and absorb with absorbent material and place into containers for later disposal. Dispose of according to local, and Provincial regulations for products containing petroleum distillates.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Put on appropriate personal equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Keep in original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container. Wash thoroughly after handling.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials(see Section 10) and food and drink. Do not store under freezing conditions or above 49 C (120 F). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Keep out of reach from children.

#### Specific end use(s)

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### 1. Heptane (CAS: 142-82-5)

## Safety Data Sheet GAP Brake Cleaner

PEL (Inhalation): 500 ppm; USA (OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL (Inhalation): 2,000 mg/m<sup>3</sup>; USA (OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL (Inhalation): 400 ppm, (ST) 500 ppm; USA (OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

REL (Inhalation): 85 ppm, (ST) 440 ppm [15-min]; USA (NIOSH)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 2. Carbon dioxide (CAS: 124-38-9)

PEL (Inhalation): 5000 ppm (OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL (Inhalation): 9000 mg/m<sup>3</sup> (OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL (Inhalation): 5000 ppm, (ST) 30,000 ppm (Cal/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

REL (Inhalation): 5000 ppm, (ST) 30,000 ppm (NIOSH)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

IOELV-LTEL (Inhalation): 9000 mg/m<sup>3</sup>; EU (EU/OSHA)  
List no. 2 under Council Directive 98/24/EC as amended. List last updated on 8/25/2023.

IOELV-LTEL (Inhalation): 5000 ppm; EU (EU/OSHA)  
List no. 2 under Council Directive 98/24/EC as amended. List last updated on 8/25/2023.

PEL (Inhalation): 5000 ppm; US (US/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL (Inhalation): 9000 mg/m<sup>3</sup>; US (US/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 3. Acetone (CAS: 67-64-1 EC: 200-662-2)

IOELV-LTEL (Inhalation): 1210 mg/m<sup>3</sup>; EU (EU/OSHA)  
List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-LTEL (Inhalation): 500 ppm; EU (EU/OSHA)  
List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

PEL (Inhalation): 1000 ppm; US (US/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL (Inhalation): 2400 mg/m<sup>3</sup>; US (US/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL (Inhalation): 500 ppm, (ST) 750 ppm, (C) 3000 ppm; US (Cal/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

REL (Inhalation): 250 ppm; US (NIOSH)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 4. Heptane (CAS: 142-82-5 EC: 205-563-8)

IOELV-LTEL (Inhalation): 2085 mg/m<sup>3</sup>; EU (EU/OSHA)  
List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-LTEL (Inhalation): 500 ppm; EU (EU/OSHA)  
List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

## Safety Data Sheet GAP Brake Cleaner

PEL [Heptane (n-Heptane)] (Inhalation): 500 ppm; US (US/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL [Heptane (n-Heptane)] (Inhalation): 2000 mg/m<sup>3</sup>; US (US/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL [Heptane (n-Heptane)] (Inhalation): 400 ppm, (ST) 500 ppm; US (Cal/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

REL [Heptane (n-Heptane)] (Inhalation): 85 ppm, (ST) 440 ppm [15-min]; US (NIOSH)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 8.2 Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

### 8.3 Individual protection measures, such as personal protective equipment (PPE)

#### Eye/face protection

Splash goggles

#### Skin protection

Chemical resistant gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Wash and dry hands after use.

#### Body protection

Skin Protection: Protective gloves (for hands). Long sleeve shirts and pants should be worn to protect exposed skin.

#### Respiratory protection

Recommended: Dust mask or Respirator should be worn if product is used in confined space or used for a prolonged period of time.

## SECTION 9: Physical and chemical properties

Appearance, such as physical state and colour	Clear liquid
Odour	Aromatic odour
Odour threshold	
pH	Not Available
Melting point and freezing point	Not Available
Initial boiling point and boiling range	98C
Flash point	-8 °C
Evaporation rate	2.8 (l'eau = 1)
Flammability, in the case of solids and gases	Extremely flammable aerosol
Upper and lower flammability or explosive limits	12.7% (upper); 2% (lower)
Vapour pressure	48mbar @ 20C
Vapour density	3.5
Relative density	0.700 @ 15 °C
Solubility	Insoluble in water
Partition coefficient — n-octanol/water	Not Determined
Auto-ignition temperature	399 °C
Decomposition temperature	Not Determined
Viscosity	< 14 centistokes at 40°C

#### Additional properties

Colour Clear

# Safety Data Sheet

## GAP Brake Cleaner

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

None under normal use conditions.

#### 10.2 Chemical stability

Stable under recommended storage conditions.

#### 10.3 Possibility of hazardous reactions

Will not occur.

#### 10.4 Conditions to avoid

Heat, flames and sparks.

#### 10.5 Incompatible materials

Avoid contact with acids and strong oxidizers such as permanganate, chlorine, ectoderm. Do not store near acids, carbon dioxide (CO<sub>2</sub>), and strong oxidizers such as permanganate, chlorine, ectoderm.

-----

Acetone: Bases, Oxidizing agents, Reducing agents, Acetone reacts violently with phosphorous oxychloride.

#### 10.6 Hazardous decomposition products

After water evaporates, burning may produce oxides of carbon, traces of sulfur and nitrogen oxides and various hydrocarbons

### SECTION 11: Toxicological information

#### Information on toxicological effects

##### Acute toxicity

ACETONE

LD50 Skin - Guinea pig - 7,429 mg/kg

LC50 Inhalation - Rat - 50,100 mg/m<sup>3</sup> - 8 h

Remarks: Drowsiness Dizziness Unconsciousness

LD50 Oral - Rat - 5,800 mg/kg

Remarks: Behavioral :Altered sleep time (including change in righting reflex). Behavioral:Tremor. Behavioral:Headache.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Remarks: RTECS: AL3150000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Kidney - Irregularities - Based on Human Evidence

Skin - Dermatitis - Based on Human Evidence

Kidney - Irregularities - Based on Human Evidence

Skin - Dermatitis - Based on Human Evidence

Remarks: This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

## Safety Data Sheet GAP Brake Cleaner

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

OECD Test Guideline 301B

Result: 91% -Readily biodegradable.

LC50 - Oncorhynchus mykiss (rainbow trout) - 5,540 mg/l - 96 h

### Skin corrosion/irritation

Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.

### Serious eye damage/irritation

Can cause severe irritation, redness, tearing, blurred vision.

### Respiratory or skin sensitization

Excessive inhalation of vapors can cause nasal and respiratory irritation and central nervous system effects including dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

### Germ cell mutagenicity

No data available

### Carcinogenicity

Carcinogenicity: Ingredients not listed by OSHA, NTP, IARC.

### Reproductive toxicity

No data available

### Summary of evaluation of the CMR properties

Not Available

### Specific target organ toxicity (STOT) - single exposure

Primary route of entry: A) Skin B) Inhalation

### Specific target organ toxicity (STOT) - repeated exposure

Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to product.

### Additional information

-----

Heptane: guinea pig LC inhalation > 17937ppm/4H (17937ppm) National Technical Information Service. Vol. OTS0556754,

human TLo inhalation 1000ppm/6M (1000ppm) BEHAVIORAL: "HALLUCINATIONS, DISTORTED PERCEPTIONS" "U.S. Bureau of Mines Report of Investigation No. 2979," Patty, F.A., and W.P. Yant, 1929 Vol. 2979, Pg. -, 1929.

mouse LLo inhalation 59gm/m3/41M (59000mg/m3) BEHAVIORAL: CONVULSIONS OR EFFECT ON SEIZURE THRESHOLD Biochemische Zeitschrift. Vol. 115, Pg. 235, 1921.

mouse LD50 intravenous 222mg/kg (222mg/kg) Journal of Pharmaceutical Sciences. Vol. 67, Pg. 566, 1978.

Link to PubMed

rat LC50 inhalation 103gm/m3/4H (103000mg/m3) Gigiena Truda i Professional'nye Zablevaniya. Labor Hygiene and Occupational Diseases. Vol. 32(10), Pg. 23, 1988.

-----

## Safety Data Sheet GAP Brake Cleaner

### Acetone: \*TOXICITY:

typ. dose mode specie amount units other

TCLo ihl man 440 ug/m3/6M

TCLo ihl man 10 mg/m3/6H

TCLo ihl hmn 500 ppm

TCLo ihl man 12000 ppm/4H

LDLo unr man 1159 mg/kg

LDLo ipr rat 500 mg/kg

LD50 orl mus 3000 mg/kg

LCLo ihl mus 110 gm/m3/1H

LD50 ipr mus 1297 mg/kg

LDLo orl dog 8 gm/kg

LD50 orl rat 5800 mg/kg

LC50 ihl rat 50100 mg/m3/8H

LDLo ipr dog 8 gm/kg

LDLo scu dog 5 gm/kg

LD50 skn rbt 20 gm/kg

LDLo scu gpg 5000 mg/kg

TDLo orl man 2857 mg/kg

LD50 ivn rat 5500 mg/kg

LDLo ivn rbt 1576 mg/kg

LD50 orl rbt 5340 mg/kg

LDLo ivn mus 4 gm/kg

\*AQTX/TLM96: Not available

### \*SAX TOXICITY EVALUATION:

THR: Moderately toxic by various routes. A skin and severe eye irritant. Human systemic effects by inhalation and ingestion. Narcotic in high concentrations. In industry, no injurious effects have been reported other than skin irritation resulting from its defatting action, or headache from prolonged inhalation. A common air contaminant. Dangerous disaster hazard due to fire and explosion hazard.

\*CARCINOGENICITY: Not available

### \*MUTATION DATA:

test lowest dose | test lowest dose

----- | -----

cyt-ham:fbr 40 gm/L | sln-smc 47600 ppm

### \*TERATOGENICITY:

Reproductive Effects Data:

TCLo: ihl-mam 31500 ug/m3/24H (1-13D preg)

### \*STANDARDS, REGULATIONS & RECOMMENDATIONS:

OSHA: Federal Register (1/19/89) and 29 CFR 1910.1000 Subpart Z

Transitional Limit: PEL-TWA 1000 ppm [015,327,545,610]

Final Limit: PEL-TWA 750 ppm; STEL 1000 ppm [015,327,545,610]

OSHA STEL does not apply to the acetate fiber industry; it is in effect for all other sectors [610]

ACGIH: TLV-TWA 750 ppm; STEL 1000 ppm [015,415,421,610]

NIOSH Criteria Document: Recommended exposure limit to this class of

# Safety Data Sheet

## GAP Brake Cleaner

compounds-air: TWA 590 mg/m3 [015]

NFPA Hazard Rating: Health (H): 1

Flammability (F): 3

Reactivity (R): 0

H1: Materials only slightly hazardous to health (see NFPA for details).

F3: Materials which can be ignited under almost all normal temperature conditions (see NFPA for details).

R0: Materials which are normally stable even under fire exposure conditions and which are not reactive with water (see NFPA for details).

### \*OTHER TOXICITY DATA:

Skin and Eye Irritation Data:

eye-hmn 500 ppm

skn-rbt 395 mg open MLD

eye-rbt 3950 ug SEV

eye-rbt 20 mg/24H MOD

skn-rbt 500 mg/24H MLD

Standards and Regulations: DOT-Hazard: Flammable liquid; Label: Flammable liquid

Status: NIOSH Analytical Methods: see Ketones I, 1300

EPA TSCA Chemical Inventory, 1986

EPA TSCA Test Submission (TSCATS) Data Base, June 1988

EPA Genetox Program 1988, Negative: SHE-clonal assay; Cell transform.-mouse embryo

EPA Genetox Program 1988, Negative: Cell transform.-RLV F344 rat embryo

EPA Genetox Program 1988, Negative: In vitro cytogenetics-nonhuman

EPA Genetox Program 1988, Negative: Histidine reversion-Ames test; In vitro SCE-nonhuman

Meets criteria for proposed OSHA Medical Records Rule

## SECTION 12: Ecological information

### Toxicity

ECOTOXICOLOGICAL INFORMATION: Not Available ENVIRONMENTAL DATA: No known significant effects or critical hazards

ECOTOXICOLOGICAL INFORMATION: Not Available

## SECTION 13: Disposal considerations

### Disposal methods

### Product disposal

Dispose of accordance in local, and provincial regulations for solvent materials.

## SECTION 14: Transport information

14.1	UN Number	None
14.2	UN Proper Shipping Name	None
14.3	Transport hazard class(es)	None
14.4	Packing group	None
14.5	Environmental hazards	None

**Safety Data Sheet  
GAP Brake Cleaner**

- |      |  |      |
|------|--|------|
| 14.6 | Special precautions for user                   | None |
| 14.7 | Transport in bulk according to IMO instruments | None |

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations specific for the product in question**

**Canadian Domestic Substances List (DSL)**

**Canadian Domestic Substances List (DSL)**

**Canadian Domestic Substances List (DSL)**

Chemical name: Carbon dioxide

CAS number: 124-38-9

**US EPA TSCA public inventory**

Chemical name: Carbon dioxide

CAS number: 124-38-9

**Massachusetts Right To Know Components**

Chemical name: Acetone

CAS number: 67-64-1

**New Jersey Right To Know Components**

Common name: ACETONE

CAS number: 67-64-1

**Pennsylvania Right To Know Components**

Chemical name: 2-Propanone

CAS number: 67-64-1

**SARA 311/312 Hazards**

Fire Hazard, Acute Health Hazard, Chronic Health Hazard for: Acetone.

**Canadian Domestic Substances List (DSL)**

Chemical name: 2-Propanone

CAS number: 67-64-1

**US EPA TSCA public inventory**

Chemical name: Acetone

CAS number: 67-64-1

**Canadian Domestic Substances List (DSL)**

Chemical name: Heptane

CAS number: 142-82-5

**US EPA TSCA public inventory**

# Safety Data Sheet

## GAP Brake Cleaner

Chemical name: Heptane

CAS number: 142-82-5

### SECTION 16: Other information

#### 16.1 Further information/disclaimer

These SDS are written in an effort to provide information to the worker in the workplace and in such a way it can be understood. To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

#### 16.2 Preparation information

Prepared by: C. Gourley