



## GAP PROFESSIONAL PRODUCTS

### Safety Data Sheet GAP Diesel Soot Cleaner

#### SECTION 1: Identification

##### 1.1 GHS Product identifier

Product name	GAP Diesel Soot Cleaner
Product number	30519
Brand	GAP Professional Products

##### 1.3 Recommended use of the chemical and restrictions on use

Diesel Fuel System Cleaner  
Professional Automotive, Industrial, or Commercial uses Only. Not for general consumer use.

##### 1.4 Supplier's details

Name	GAP Professional Products
Address	122 Route 105 Keswick Ridge NB E6L 1B1 Canada
Telephone	(506) 363-9708
Fax	(506) 363-4241
email	info@gapauto.com

##### 1.5 Emergency phone number

For Medical or Transport Emergencies  
CANUTEC (24 Hours)  
(613) 996-6666

#### SECTION 2: Hazard identification

##### 2.1 Classification of the substance or mixture

###### GHS classification in accordance with: WHMIS 2015

- Serious eye damage/eye irritation, Cat. 2B
- Skin corrosion/irritation, Cat. 2
- Skin sensitizer, Cat. 1
- Carcinogenicity, Cat. 1B
- Acute toxicity, inhalation, Cat. 5
- Acute toxicity, oral, Cat. 5
- Carcinogenicity, Cat. 2
- Serious eye damage/eye irritation, Cat. 2
- Acute toxicity, oral, Cat. 4

# Safety Data Sheet

## GAP Diesel Soot Cleaner

- Serious eye damage/eye irritation, Cat. 1
- Acute toxicity, inhalation, Cat. 4
- Specific target organ toxicity following repeated exposure, Cat. 2

### 2.2 GHS label elements, including precautionary statements

#### Pictograms



1. Exclamation mark; 2. Health hazard; 3. Corrosion

#### Signal word

**Danger**

#### Hazard statement(s)

H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H350	May cause cancer [route]
H351	Suspected of causing cancer [route]
H373	May cause damage to organs [organs] through prolonged or repeated exposure [route]

#### Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash ... thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/...if you feel unwell,
P302+P352	IF ON SKIN: Wash with plenty of water/...
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a POISON CENTER/doctor/...
P312	Call a POISON CENTER/doctor/... if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see ... on this label).
P330	Rinse mouth.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P501	Dispose of contents/container to ...

# Safety Data Sheet

## GAP Diesel Soot Cleaner

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Hazardous components

Component	Concentration
<b>Solvent naphtha (petroleum), heavy arom (CAS no.: 64742-94-5)</b>	<b>30 - &lt; 60 % (weight)</b>
CLASSIFICATIONS: No data available. HAZARDS: No data available.	
<b>Nitric acid, 2-ethylhexyl ester (CAS no.: 27247-96-7; EC no.: 248-363-6)</b>	<b>&gt; 15 - &lt; 30 % (weight)</b>
CLASSIFICATIONS: No data available. HAZARDS: No data available.	
<b>XYLENES (MIXED) (CAS no.: 1330-20-7; EC no.: 215-535-7; Index no.: 601-022-00-9)</b>	<b>&gt; 5 - &lt; 15 % (weight)</b>
CLASSIFICATIONS: Flammable liquids, Cat. 3; Acute toxicity, inhalation, Cat. 4; Acute toxicity, dermal, Cat. 4; Skin corrosion/irritation, Cat. 2. HAZARDS: H226 - Flammable liquid and vapor; H312 - Harmful in contact with skin; H315 - Causes skin irritation; H332 - Harmful if inhaled. [SCLs/M-factors/ATEs]: *	
<b>NAPHTHALENE (CAS no.: 91-20-3; EC no.: 202-049-5; Index no.: 601-052-00-2)</b>	<b>&gt; 5 - &lt; 10 % (weight)</b>
CLASSIFICATIONS: Carcinogenicity, Cat. 2; Acute toxicity, oral, Cat. 4; Hazardous to the aquatic environment, short-term (acute), Cat. 1; Hazardous to the aquatic environment, long-term (chronic), Cat. 1. HAZARDS: H302 - Harmful if swallowed; H351 - Suspected of causing cancer [route]; H400 - Very toxic to aquatic life; H410 - Very toxic to aquatic life with long lasting effects.	
<b>1,2,3-trimethylbenzene (CAS no.: 526-73-8; EC no.: 208-394-8)</b>	<b>&gt; 1 - &lt; 3 % (weight)</b>
CLASSIFICATIONS: No data available. HAZARDS: No data available.	
<b>1,2,4-trimethylbenzene (CAS no.: 95-63-6; EC no.: 202-436-9; Index no.: 601-043-00-3)</b>	<b>&gt; 1 - &lt; 3 % (weight)</b>
CLASSIFICATIONS: Flammable liquids, Cat. 3; Acute toxicity, inhalation, Cat. 4; Specific target organ toxicity, single exposure, Cat. 3; Skin corrosion/irritation, Cat. 2; Eye damage/irritation, Cat. 2; Hazardous to the aquatic environment, long-term (chronic), Cat. 2. HAZARDS: H226 - Flammable liquid and vapor; H315 - Causes skin irritation; H319 - Causes serious eye irritation; H332 - Harmful if inhaled; H335 - May cause respiratory irritation; H411 - Toxic to aquatic life with long lasting effects.	
<b>Cumene (CAS no.: 98-82-8; EC no.: 202-704-5; Index no.: 601-024-00-X)</b>	<b>&gt; 1 - &lt; 3 % (weight)</b>
CLASSIFICATIONS: Flammable liquids, Cat. 3; Aspiration hazard, Cat. 1; Specific target organ toxicity, single exposure, Cat. 3; Hazardous to the aquatic environment, long-term (chronic), Cat. 2. HAZARDS: H226 - Flammable liquid and vapor; H304 - May be fatal if swallowed and enters airways; H335 - May cause respiratory irritation; H411 - Toxic to aquatic life with long lasting effects.	
<b>ETHYLBENZENE (CAS no.: 100-41-4; EC no.: 202-849-4; Index no.: 601-023-00-4)</b>	<b>&gt; 1 - &lt; 5 % (weight)</b>
CLASSIFICATIONS: Acute toxicity, inhalation, Cat. 4; Specific target organ toxicity, repeated exposure, Cat. 2; Flammable liquids, Cat. 2; Aspiration hazard, Cat. 1. HAZARDS: H225 - Highly flammable liquid and vapor; H304 - May be fatal if swallowed and enters airways; H332 - Harmful if inhaled; H373 - May cause damage to organs [organs] through prolonged or repeated exposure [route].	

### SECTION 4: First-aid measures

#### 4.1 Description of necessary first-aid measures

If inhaled	If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet, and get medical attention
In case of skin contact	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician if symptoms occur. Wash contaminated clothes before reuse
In case of eye contact	Rinse thoroughly with plenty of water for at least 15 minutes. Remove contact lenses if easy to do. Get medical attention if symptoms occur.
If swallowed	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms/effects, acute and delayed

Mild tissue inflammation, rash, nausea.

#### 4.3 Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

# Safety Data Sheet

## GAP Diesel Soot Cleaner

### SECTION 5: Fire-fighting measures

#### 5.1 Suitable extinguishing media

Treat surrounding material. Regular foam, Water Spray, Water Fog, carbon dioxide or dry chemical. Spray using fog nozzles. Keep containers cool with water. Use caution when applying carbon dioxide in confined spaces.

#### 5.2 Specific hazards arising from the chemical

Vapors/fumes may be irritating, corrosive, and/or toxic. Fire fighters must be protected from smoke with self contained breathing apparatus. Heavy smoke may obscure vision. Smoke may contain oxides of carbon, nitrogen, sulfur, and chlorine.

#### 5.3 Special protective actions for fire-fighters

Wear full protective clothing and self-contained breathing apparatus. Use water spray to cool exposed containers.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs. See Section 8 for recommended personal protective equipment.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

LARGE SPILLS: Dike far ahead of spill to prevent further movement. Recover by pumping or by using a suitable absorbent.  
SMALL SPILLS: Contain and absorb with absorbent material and place into containers for later disposal. Wash site of spillage thoroughly with water. Dispose in suitable waste container.

#### Reference to other sections

For disposal see section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Ensure adequate ventilation. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes and clothing. Avoid ingestion and inhalation. Avoid dust formation. dust is formed. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container(s) tightly closed. Use and store this material at room temperature away from sources of ignition, heat, direct sunlight and hot surfaces. Keep away from any incompatible materials (see section 10)

#### Specific end use(s)

Store in original container. Store as directed by manufacturer

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### 1. Naphthalene (CAS: 91-20-3)

PEL (Inhalation): 10 ppm (CA/CCOHS)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL (Inhalation): 50 mg/m<sup>3</sup> (CA/CCOHS)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

## Safety Data Sheet

### GAP Diesel Soot Cleaner

PEL (Inhalation): 10 ppm, (ST) 15 ppm (Cal/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

REL (Inhalation): 10 ppm, (ST) 15 ppm (NIOSH)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### **2. Cumene (CAS: 98-82-8)**

PEL (Inhalation): 50 ppm (OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL (Inhalation): 245 mg/m<sup>3</sup> (OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL (Inhalation): 50 ppm (Cal/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

REL (Inhalation): 50 ppm (NIOSH)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

TLV<sup>®</sup> (Inhalation): 50 ppm; USA (ACGIH)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### **3. 2-butoxyethanol (CAS: 111-76-2 EC: 203-905-0)**

IOELV-LTEL (Inhalation): 98 mg/m<sup>3</sup>; EU (EU/OSHA)  
Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-LTEL (Inhalation): 20 ppm; EU (EU/OSHA)  
Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-STEL (Inhalation): 246 mg/m<sup>3</sup>; EU (EU/OSHA)  
Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-STEL (Inhalation): 50 ppm; EU (EU/OSHA)  
Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

PEL (Inhalation): 50 ppm; US (US/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL (Inhalation): 240 mg/m<sup>3</sup>; US (US/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL (Inhalation): 20 ppm; US (Cal/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

REL (Inhalation): 5 ppm; US (NIOSH)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### **4. XYLENES (MIXED) (CAS: 1330-20-7 EC: 215-535-7)**

IOELV-LTEL [Xylene, Pure] (Inhalation): 221 mg/m<sup>3</sup>; EU (EU/OSHA)  
Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-LTEL [Xylene, Pure] (Inhalation): 50 ppm; EU (EU/OSHA)  
Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-STEL [Xylene, Pure] (Inhalation): 442 mg/m<sup>3</sup>; EU (EU/OSHA)  
Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-STEL [Xylene, Pure] (Inhalation): 100 ppm; EU (EU/OSHA)  
Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

PEL [Xylenes (o-, m-, p-isomers)] (Inhalation): 100 ppm; US (US/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL [Xylenes (o-, m-, p-isomers)] (Inhalation): 435 mg/m<sup>3</sup>; US (US/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

## Safety Data Sheet GAP Diesel Soot Cleaner

PEL [Xylenes (o-, m-, p-isomers)] (Inhalation): 100 ppm, (ST) 150 ppm, (C) 300 ppm; US (Cal/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

REL [Xylenes (o-, m-, p-isomers)] (Inhalation): 100 ppm, (ST) 150 ppm; US (NIOSH)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 5. Ethylbenzene (CAS: 100-41-4 EC: 202-849-4)

IOELV-LTEL (Inhalation): 442 mg/m<sup>3</sup>; EU (EU/OSHA)

Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-LTEL (Inhalation): 100 ppm; EU (EU/OSHA)

Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-STEL (Inhalation): 884 mg/m<sup>3</sup>; EU (EU/OSHA)

Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-STEL (Inhalation): 200 ppm; EU (EU/OSHA)

Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

PEL [Ethyl benzene] (Inhalation): 100 ppm; US (US/OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL [Ethyl benzene] (Inhalation): 435 mg/m<sup>3</sup>; US (US/OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL [Ethyl benzene] (Inhalation): 5 ppm, (ST) 30 ppm; US (Cal/OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

REL [Ethyl benzene] (Inhalation): 100 ppm, (ST) 125 ppm; US (NIOSH)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 8.2 Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Showers, eyewash stations, and ventilation systems should be present and in good working order. Wash hands before breaks and at the end of workday.

### 8.3 Individual protection measures, such as personal protective equipment (PPE)

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Skin protection

Wear Nitrile gloves, chemical resistant gloves.

#### Respiratory protection

Recommended: Dust mask or Respirator should be worn if product is used in confined space or used for a prolonged period of time.

## SECTION 9: Physical and chemical properties

Appearance, such as physical state and colour	Clear slightly hazy liquid
Odour	Characteristic
Odour threshold	Not determined
pH	N/A oil based
Melting point and freezing point	< -50 °C (-58 °F)
Initial boiling point and boiling range	179 - 217 °C (354 - 423 °F)
Flash point	61 - 66 °C (142 - 151 °F)
Evaporation rate	<1 (Butyl Acetate)
Flammability, in the case of solids and gases	Not Determined
Upper and lower flammability or explosive limits	Upper explosion limit : 7 %(V)      Lower explosion limit : 0.6 %(V)
Vapour pressure	< 10 mmHg @ 20 °C (68 °F)

## Safety Data Sheet GAP Diesel Soot Cleaner

Vapour density	
Relative density	0.8-0.91 kg/l 60C
Solubility	Insoluble
Partition coefficient — n-octanol/water	Log KOW > 4 (mineral oil data)
Auto-ignition temperature	Not Determined
Decomposition temperature	Not Available
Viscosity	1.2 - 1.36 mm <sup>2</sup> /s @ 25 °C (77 °F)

### Additional properties

Physical state	Liquid
Colour	Amber
Explosive properties	Not Determined
Oxidising properties	None

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

None under normal use conditions.

### 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

Stable under normal use conditions.

### 10.4 Conditions to avoid

Avoid storing in direct sunlight and avoid extremes of temperature.

### 10.5 Incompatible materials

Strong oxidizing agents

### 10.6 Hazardous decomposition products

Oxides of carbon, oxides of sulfur, oxides of phosphorus, oxides of nitrogen, amines, aliphatic compounds, toxic by-products.

## SECTION 11: Toxicological information

### Information on toxicological effects

#### Acute toxicity

64742-94-5:

Acute oral toxicity

:

LD50 (Rat, male and female): > 5,000 mg/kg

Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity

:

LC50 (Rat, male and female): > 5.28 mg/l

Exposure time: 4 h

Test atmosphere: gas

Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity

:

// ----- From the Suggestion report (10/31/2025, 9:17 AM) ----- //

The ATE (oral) of the mixture is: 500 mg/kg bw

## Safety Data Sheet GAP Diesel Soot Cleaner

2-Butoxyethanol

LD50 Intravenous - Rat - 307 mg/kg

LD50 Skin - Rabbit - 1,060 mg/kg

Remarks: OECD Test Guideline 402

LD50 Oral - Rat - 880 mg/kg

Remarks: OECD Test Guideline 401

LC50 Inhalation - Rat - 450 ppm

Remarks: Behavioral:Ataxia. Nutritional and Gross Metabolic:Weight loss or decreased weight gain

LD50 Oral - Rat - 470 mg/kg

LDLo Intraperitoneal - Rat - 220 mg/kg

Result: IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Result: IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-Butoxyethanol)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

EC50 - Pseudokirchneriella subcapitata (green algae) - 1,840 mg/l - 72 h

Remarks: OECD Test Guideline 201

EC50 - Daphnia magna (water flea) - 1,550 mg/l - 48 h

Remarks: OECD Test Guideline 202

LC50 - Oncorhynchus mykiss (rainbow trout) - 1,474 mg/l - 96 h

Remarks: OECD Test Guideline 203

LC50 - Daphnia magna (water flea) - 1,550 mg/l - 48 h

Remarks: OECD Test Guideline 202

LC50 - Pseudokirchneriella subcapitata (green algae) - 911 mg/l - 72 h

Remarks: OECD Test Guideline 201

Alcohols, C9-11, ethoxylated

LD50 Skin - Rabbit - >2,000 mg/kg

LD50 Oral - Rat - >2,000 mg/kg

LD50 Skin - Rabbit - >5,000 mg/kg

EC50 - Algae - 10-100 mg/l - 72 h

Citation: Stepan SDS

EC50 - Daphnia magna (water flea) - 5-10 mg/l - 48 h

Citation: Stepan SDS

LC50 - Fish - 5-10 mg/l - 48 h

Citation: Stepan SDS

LC50 - Pimephales promelas (fathead minnow) - 1 - 10 mg/l - 96 h

EC50 - Daphnia magna (water flea) - 1 - 10 mg/l - 48 h

ErC50 - Algae. - 1 - 10 mg/l - 96 h

NAPHTHALENE

// ----- From the Suggestion report (12/10/2025, 12:00 PM) ----- //

The ATE (gas inhalation) of the mixture is: 19565.22 ppmV

### Skin corrosion/irritation

LD50 (Rabbit, male and female): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal toxicity

# Safety Data Sheet

## GAP Diesel Soot Cleaner

Heavy aromatic naphtha  
Inhalation - 5.28 mg/l/4h - 4h

### Serious eye damage/irritation

Not Determined

### Respiratory or skin sensitization

Acute inhalation toxicity

Heavy aromatic naphtha  
Inhalation - 5.28 mg/l/4h - 4h

:

LC50 (Rat, male and female): > 5.28 mg/l

Exposure time: 4 h

Test atmosphere: gas

Assessment: The substance or mixture has no acute inhalation toxicity

May be fatal if swallowed and enters airways.

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects.

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity

No data available

### Specific target organ toxicity (STOT) - single exposure

HYDROCRACKED PARAFFINIC MINERAL OIL: No Data Available;

AROMATIC HYDROCARBON: Cat 3 Transient Toxicant - CNS, Liver, Kidneys;

TRADE SECRET COMPONENT: Cat 3 Transient Toxicant - CNS, Liver, Kidneys

### Specific target organ toxicity (STOT) - repeated exposure

HYDROCRACKED PARAFFINIC MINERAL OIL: No Data Available;

AROMATIC HYDROCARBON: No Data Available;

TRADE SECRET COMPONENT: No Hazard

### Aspiration hazard

HYDROCRACKED PARAFFINIC MINERAL OIL: Cat 1 Aspiration Hazard;

AROMATIC HYDROCARBON: Cat 1 Aspiration Hazard;

TRADE SECRET COMPONENT: No Hazard

### Additional information

METHYL ETHYL KETONE: \*TOXICITY:

typ. dose mode specie amount units other

TCLo ihl hmn 100 ppm/5M

LC50 ihl mus 40 gm/m<sup>3</sup>/2H

LC50 ihl rat 23500 mg/m<sup>3</sup>/8H

LDLo ipr gpg 2000 mg/kg

LD50 ipr mus 616 mg/kg

LD50 orl mus 4050 mg/kg

LD50 orl rat 2737 mg/kg

LD50 skn rbt 6480 mg/kg

LC50 ihl mam 38 gm/m<sup>3</sup>

LD50 ipr rat 607 mg/kg

# Safety Data Sheet

## GAP Diesel Soot Cleaner

\*AQTX/TLM96: over 1000 ppm

**\*SAX TOXICITY EVALUATION:**

THR: Moderately toxic by ingestion, skin contact and intraperitoneal routes.

Human systemic effects by inhalation. An experimental teratogen.

Experimental reproductive effects. A strong irritant. Human eye irritation @ 350 ppm. Affects peripheral nervous system and central nervous system.

\*CARCINOGENICITY: Not available

**\*MUTATION DATA:**

test lowest dose | test lowest dose

----- | -----  
sln-smc 33800 ppm |

**\*TERATOGENICITY:**

Reproductive Effects Data:

TCLo: ihl-rat 3000 ppm/7H (6-15D preg)

TCLo: ihl-rat 1000 ppm/7H (6-15D preg)

**\*STANDARDS, REGULATIONS & RECOMMENDATIONS:**

OSHA: Federal Register (1/19/89) and 29 CFR 1910.1000 Subpart Z

Transitional Limit: PEL-TWA 200 ppm [610]

Final Limit: PEL-TWA 200 ppm; STEL 300 ppm [610]

ACGIH: TLV-TWA 200 ppm; STEL 300 ppm [015,415,421,610]

NIOSH Criteria Document: Recommended Exposure Limit to this compound-air:

TWA 200 ppm [610]

NFPA Hazard Rating: Health (H): 1

Flammability (F): 3

Reactivity (R): 0

H1: Materials only slightly hazardous to health (see NFPA for details).

F3: Materials which can be ignited under almost all normal temperature conditions (see NFPA for details).

R0: Materials which are normally stable even under fire exposure conditions and which are not reactive with water (see NFPA for details).

**\*OTHER TOXICITY DATA:**

Skin and Eye Irritation Data:

eye-hmn 350 ppm

skn-rbt 500 mg/24H MOD

skn-rbt 402 mg/24H MLD

skn-rbt 13780 ug/24H open MLD

eye-rbt 80 mg

Review: Toxicology Review

Standards and Regulations: DOT-Hazard: Flammable liquid; Label: Flammable liquid

Status: EPA Genetox Program 1988, Inconclusive: B subtilis rec assay

EPA TSCA Chemical Inventory, 1986

EPA TSCA 8(a) Preliminary Assessment Information, Final Rule

EPA TSCA Test Submission (TSCATS) Data Base, January 1989

NIOSH Analytical Methods: see 2-Butanone, 2500

NIOSH Analytical Methods: see 2-Butanone, Ethanol, and Toluene in blood, 8002

Meets criteria for proposed OSHA Medical Records Rule

-----  
NAPHTHALENE: \*TOXICITY:

## Safety Data Sheet GAP Diesel Soot Cleaner

typ. dose mode specie amount units other

LDLo orl chd 100 mg/kg

LDLo unr man 74 mg/kg

LD50 orl rat 490 mg/kg

LD50 orl mus 533 mg/kg

LD50 scu mus 969 mg/kg

LDLo orl dog 400 mg/kg

LDLo orl cat 1000 mg/kg

LDLo orl rbt 3 gm/kg

LD50 orl gpg 1200 mg/kg

LDLo unr hmh 29 mg/kg

LD50 ipr mus 150 mg/kg

LD50 ivn mus 100 mg/kg

\*AQTX/TLM96: Not available

\*SAX TOXICITY EVALUATION:

THR: Human poison by ingestion and possibly other routes. Experimental poison by ingestion, intravenous and intraperitoneal routes. Moderately toxic by subcutaneous route. An experimental tumorigen. Experimental reproductive effects. Mutagenic data. An eye and skin irritant.

\*CARCINOGENICITY:

Tumorigenic Data:

TDLo: scu-rat 3500 mg/kg/12W-I

Status: NTP Carcinogenesis Studies; on test (two year studies), January 1988

\*MUTATION DATA:

test lowest dose | test lowest dose

----- | -----

Not available |

\*TERATOGENICITY:

Reproductive Effects Data:

TDLo: ipr-rat 5925 mg/kg (1-15D preg)

TDLo: orl-mus 2400 mg/kg (7-14D preg)

\*STANDARDS, REGULATIONS & RECOMMENDATIONS:

OSHA: Federal Register (1/19/89) and 29 CFR 1910.1000 Subpart Z

Transitional Limit: PEL-TWA 10 ppm [610]

Final Limit: PEL-TWA 10 ppm; STEL 15 ppm [610]

ACGIH: TLV-TWA 10 ppm; STEL 15 ppm [015,414,421,610]

NIOSH Criteria Document: None

NFPA Hazard Rating: Health (H): 2

Flammability (F): 2

Reactivity (R): 0

H2: Materials hazardous to health, but areas may be entered freely with full-faced mask self-contained breathing apparatus which provides eye protection (see NFPA for details).

F2: Materials which must be moderately heated before ignition will occur (see NFPA for details).

R0: Materials which are normally stable even under fire exposure conditions and which are not reactive with water (see NFPA for details).

\*OTHER TOXICITY DATA:

Skin and Eye Irritation Data:

skn-rbt 495 mg open MLD

eye-rbt 100 mg MLD

## Safety Data Sheet GAP Diesel Soot Cleaner

Review: Toxicology Review-2  
Standards and Regulations: DOT-Hazard: ORM-A; Label: None  
DOT-IMO: Flammable solid; Label: Flammable solid  
Status: EPA Genetox Program 1988, Negative: Cell transform.-mouse embryo  
EPA Genetox Program 1988, Negative: Cell transform.-RLV F344 rat embryo  
EPA Genetox Program 1988, Negative: Histidine reversion-Ames test  
EPA TSCA Chemical Inventory, 1986  
EPA TSCA Test Submission (TSCATS) Data Base, June 1988  
NIOSH Analytical Methods: see Hydrocarbons, Aromatic, 1501;  
NIOSH Analytical Methods: see Polynuclear Aromatic Hydrocarbons (HPLC), 5506; (GC), 5515  
Meets criteria for proposed OSHA Medical Records Rule  
IDLH value: 500 ppm [346,371]  
Fatal dose: 5-15 g [071]

-----

Cumene: human TCLo inhalation 200ppm (200ppm) BEHAVIORAL: SOMNOLENCE (GENERAL DEPRESSED ACTIVITY)

BEHAVIORAL: ANTIPSYCHOTIC

BEHAVIORAL: IRRITABILITY "Handbook of Organic Industrial Solvents," 2nd ed., Chicago, National Assoc. of Mutual Casualty Companies, 1961Vol. 2, Pg. 39, 1961.

mouse LC50 inhalation 10gm/m3/7H (10000mg/m3) LIVER: MULTIPLE EFFECTS

KIDNEY, URETER, AND BLADDER: CHANGES IN BOTH TUBULES AND GLOMERULI

BLOOD: CHANGES IN SPLEEN Journal of Industrial Hygiene and Toxicology. Vol. 26, Pg. 264, 1944.

mouse LD50 oral 12750mg/kg (12750mg/kg) Gigena i Sanitariya. For English translation, see HYSAAV. Vol. 36(9), Pg. 18, 1971.

rabbit LD50 skin 12300uL/kg (12.3mL/kg) AMA Archives of Industrial Hygiene and Occupational Medicine. Vol. 4, Pg. 119, 1951.

rat LCLo inhalation 8000ppm/4H (8000ppm) AMA Archives of Industrial Hygiene and Occupational Medicine. Vol. 4, Pg. 119, 1951.

rat LD50 oral 1400mg/kg (1400mg/kg) GASTROINTESTINAL: GASTRITIS AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956.

-----

XYLENES (MIXED): \*TOXICITY:

typ. dose mode specie amount unit other

TCLo ihl hmn 200 ppm

LCLo ihl man 10000 ppm/6H

LD50 orl rat 4300 mg/kg

LC50 ihl rat 5000 ppm/4H

LD50 scu rat 1700 mg/kg

LD50 ipr mus 1548 mg/kg

LDLo ipr gpg 2000 mg/kg

LDLo ipr mam 2000 mg/kg

LCLo ihl gpg 450 ppm

LDLo orl hmn 50 mg/kg

\*AQTX/TLM96: 100-10 ppm

\*SAX TOXICITY EVALUATION:

THR = MODERATE via inhalation and oral routes.

\*CARCINOGENICITY:

# Safety Data Sheet

## GAP Diesel Soot Cleaner

Review: IARC Cancer Review: Human Inadequate Evidence  
IARC Cancer Review: Animal Inadequate Evidence  
IARC: Not classifiable as a human carcinogen (Group 3) [610]  
Status: NTP Carcinogenesis Studies (Gavage); No Evidence: Male and Female Rat,  
Male and Female Mouse [620]

### \*MUTATION DATA:

test lowest dose | test lowest dose

----- | -----  
cyt-smc 1 mmol/tube |

### \*TERATOGENICITY:

Reproductive Effects Data:

TCLo: ihl-rat 1000 mg/m<sup>3</sup>/24H (9-14D preg)

TCLo: ihl-rat 50 mg/m<sup>3</sup>/6H (1-21D preg)

TCLo: ihl-rat 600 mg/m<sup>3</sup>/24H (7-15D preg)

TDLo: orl-mus 20600 ug/kg (6-15D preg)

TCLo: ihl-mus 4000 ppm/6H (6-12D preg)

TDLo: orl-mus 31 mg/kg (6-15D preg)

TCLo: ihl-mus 2000 ppm/6H (6-12D preg)

### \*STANDARDS, REGULATIONS & RECOMMENDATIONS:

OSHA: Federal Register (1/19/89) and 29 CFR 1910.1000 Subpart Z

Transitional Limit: PEL-TWA 100 ppm [610]

Final Limit: PEL-TWA 100 ppm; STEL 150 ppm [610]

ACGIH: TLV-TWA 100 ppm; STEL 150 ppm [610]

NIOSH Criteria Document: Recommended Exposure Limit to this compound-air:

TWA 100 ppm; Ceiling Limit 200 ppm/10M [015,610]

NFPA Hazard Rating: Health (H): 2

Flammability (F): 3

Reactivity (R): 0

H2: Materials hazardous to health, but areas may be entered freely with full-faced mask self-contained breathing apparatus which provides eye protection (see NFPA for details).

F3: Materials which can be ignited under almost all normal temperature conditions (see NFPA for details).

R0: Materials which are normally stable even under fire exposure conditions and which are not reactive with water (see NFPA for details).

### \*OTHER TOXICITY DATA:

Skin and Eye Irritation Data:

eye-hmn 200 ppm

skn-rbt 100% MOD

skn-rbt 500 mg/24H MOD

eye-rbt 87 mg MLD

eye-rbt 5 mg/24H SEV

Standards and Regulations: DOT-Hazard: Flammable liquid; Label: Flammable liquid

DOT-IMO: Flammable or Combustible liquid; Label: Flammable liquid

Status: NIOSH Analytical Methods: see hydrocarbons, aromatic, 1501

EPA TSCA Chemical Inventory, 1986

EPA TSCA 8(a) Preliminary Assessment Information, Final Rule

EPA Genetox Program 1986, Negative: In vitro SCE-human lymphocytes;

In vitro SCE-human

EPA TSCA Test Submission (TSCATS) Data Base, December 1986

Meets criteria for proposed OSHA Medical Records Rule

# Safety Data Sheet

## GAP Diesel Soot Cleaner

-----

### GLYCOL ETHER EB: \*TOXICITY:

typ. dose mode specie amount units other

TCLo ihl hmn 195 ppm/8H

LD50 orl rat 1480 mg/kg

LC50 ihl rat 450 ppm/4H

LD50 ipr rat 220 mg/kg

LD50 ivn rat 340 mg/kg

LD50 orl mus 1230 mg/kg

LC50 ihl mus 700 ppm/7H

LD50 ipr mus 536 mg/kg

LDLo scu mus 500 mg/kg

LD50 ivn mus 1130 mg/kg

LD50 orl rbt 320 mg/kg

LD50 skn rbt 490 mg/kg

LD50 ivn rbt 280 mg/kg

LD50 orl gpg 1200 mg/kg

LD50 skn gpg 230 mg/kg

LD50 ipr rbt 220 mg/kg

\*AQTX/TLM96: 1000-100 ppm

### \*SAX TOXICITY EVALUATION:

THR = HIGH human irritant via inhalation. HIGH via intravenous, oral and dermal routes. MODERATE via oral, intraperitoneal, inhalation, subcutaneous and dermal routes. MILD skin and eye irritant.

\*CARCINOGENICITY: Not available

### \*MUTATION DATA:

test lowest dose | test lowest dose

----- | -----

Not available |

### \*TERATOGENICITY:

Reproductive Effects Data:

TCLo: ihl-rat 200 ppm/6H (6-15D preg)

TCLo: ihl-rat 25 ppm/6H (6-15D preg)

TDLo: orl-mus 9440 mg/kg (7-14D preg)

TCLo: ihl-rbt 200 ppm/6H (6-18D preg)

TCLo: ihl-rbt 100 ppm/6H (6-18D preg)

### \*STANDARDS, REGULATIONS & RECOMMENDATIONS:

OSHA: Federal Register (1/19/89) and 29 CFR 1910.1000 Subpart Z

Transitional Limit: PEL-TWA 50 ppm (skin) [610]

Final Limit: PEL-TWA 25 ppm (skin) [610]

ACGIH: TLV-TWA 25 ppm (skin) [610]

NIOSH Criteria Document: None

NFPA Hazard Rating: Health (H): 2

Flammability (F): 2

Reactivity (R): 0

H2: Materials hazardous to health, but areas may be entered freely with full-faced mask self-contained breathing apparatus which provides eye protection (see NFPA for details).

F2: Materials which must be moderately heated before ignition will occur (see NFPA for details).

R0: Materials which are normally stable even under fire exposure conditions

## Safety Data Sheet GAP Diesel Soot Cleaner

and which are not reactive with water (see NFPA for details).

**\*OTHER TOXICITY DATA:**

Skin and Eye Irritation Data:

skn-rbt 500 mg open MLD

eye-rbt 18 mg

Standards and Regulations: DOT-IMO: Poison B; Label: St. Andrew's Cross,  
Flammable liquid

Status: "NIOSH Manual of Analytical Methods, 3rd. Ed."

Reported in EPA TSCA Inventory, 1983

EPA TSCA Section 8(e) Status Report 8EHQ-0483-0475

Meets criteria for proposed OSHA Medical Records Rule

-----  
**ETHYLBENZENE: \*TOXICITY:**

typ. dose mode specie amount unit other

TCLo ihl hmn 100 ppm/8H

LD50 orl rat 3500 mg/kg

LCLo ihl rat 4000 ppm/4H

LD50 skn rbt 17800 mg/kg

LCLo ihl gpg 10000 ppm

\*AQTX/TLM96: 100-10 ppm.

**\*SAX TOXICITY EVALUATION:**

THR: MODERATE via irritation to the skin, eyes and mucous membranes, and via oral and inhalation routes. A concentration of 0.19% vapor in air will irritate eyes; 0.2% is extremely irritating. An experimental teratogen.

**\*CARCINOGENICITY:**

Status: NTP Carcinogenesis Studies; selected but deferred, April 1984

**\*MUTATION DATA:**

test lowest dose

-----  
sce-hmn:lym 1 mmol/L

**\*TERATOGENICITY:**

Reproductive Effects Data:

TCLo: ihl-rat 97 ppm/7H (15D preg)

TCLo: ihl-rat 985 ppm/7H (1-19D preg)

TCLo: ihl-rat 96 ppm/7H (1-19D preg)

TCLo: ihl-rbt 99 ppm/7H (1-18D preg)

**\*STANDARDS, REGULATIONS & RECOMMENDATIONS:**

OSHA: Federal Register (1/19/89) and 29 CFR 1910.1000 Subpart Z

Transitional Limit: PEL-TWA 100 ppm [610]

Final Limit: PEL-TWA 100 ppm, STEL 125 ppm [610]

ACGIH: TLV-TWA 100 ppm, STEL 125 ppm [610]

NIOSH Criteria Document: None

NFPA Hazard Rating: Health (H): 2

Flammability (F): 3

Reactivity (R): 0

H2: Materials hazardous to health, but areas may be entered freely with full-faced mask self-contained breathing apparatus which provides eye protection (see NFPA for details).

F3: Materials which can be ignited under almost all normal temperature

## Safety Data Sheet GAP Diesel Soot Cleaner

conditions (see NFPA for details).

R0: Materials which are normally stable even under fire exposure conditions and which are not reactive with water (see NFPA for details).

**\*OTHER TOXICITY DATA:**

Skin and Eye Irritation Data:

skn-rbt 15 mg/24H open MLD

eye-rbt 100 mg

Standards and Regulations: DOT-Hazard: Flammable liquid; Label: Flammable liquid

Status: "NIOSH Manual of Analytical Methods, 3rd. Ed."

Reported in EPA TSCA Inventory, 1983

EPA TSCA 8(a) Preliminary Assessment Information Final Rule

EPA Genetic Toxicology Program, January 1984

EPA TSCA Section 8(e) Status Report 8EHQ-0680-0345

EPA TSCA Section 8(e) Status Report 8EHQ-1080-0368

Meets criteria for proposed OSHA Medical Records Rule

### SECTION 12: Ecological information

**Toxicity**

ENVIRONMENTAL DATA: No known significant effects or critical hazards

ECOTOXICOLOGICAL INFORMATION: Not Available

**Persistence and degradability**

Hydrocarbon mineral oils, and non-petroleum oils, are inherently biodegradable and are not persistent. OECD 301 values range from 50% to 95% in 28 days.

**Bioaccumulative potential**

Hydrocarbon mineral oils, and non-petroleum oils, are inherently biodegradable and have low bioaccumulation potential. Specific information on components is shown below.

**Mobility in soil**

Mineral oils have been shown to adhere strongly to soil. Mobility is expected to be low.

**Other adverse effects**

None

### SECTION 13: Disposal considerations

**Disposal methods**

**Product disposal**

Dispose of accordance in local, and provincial regulations for solvent and oil materials

**Packaging disposal**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Other disposal recommendations**

Prevent the material from entering drains and water courses. Do not discharge directly to a water source. Advise Authorities if spillage has entered watercourse or sewer or has contaminated soil or vegetation.

### SECTION 14: Transport information

**DOT (US)**

Not dangerous goods

**Safety Data Sheet**  
**GAP Diesel Soot Cleaner**

**IMDG**

Not dangerous goods

**IATA**

Not dangerous goods

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations specific for the product in question**

**Canadian Domestic Substances List (DSL)**

All components of this product are listed on the Canadian Domestic Substance List

**Canadian Non-Domestic Substances List (NDSL)**

**Pennsylvania Right To Know Components**

Ethylene glycol monobutyl ether

CAS: 111-76-2 for: GLYCOL ETHER EB.

**New Jersey Right To Know Components**

Ethylene glycol monobutyl ether

CAS: 111-76-2 for: GLYCOL ETHER EB.

**Massachusetts Right To Know Components**

Ethylene glycol monobutyl ether

CAS: 111-76-2 for: GLYCOL ETHER EB.

**Canadian Domestic Substances List (DSL)**

Chemical name: Ethanol, 2-butoxy-

CAS number: 111-76-2

**US EPA TSCA public inventory**

Chemical name: GLYCOL ETHER EB

CAS number: 111-76-2

**Canadian Domestic Substances List (DSL)**

Chemical name: Alcohols, C9-11, ethoxylated

CAS number: 68439-46-3

**US EPA TSCA public inventory**

Chemical name: Alcohols, C9-11, ethoxylated

CAS number: 68439-46-3

**Canadian Domestic Substances List (DSL)**

Chemical name: Nitric acid, 2-ethylhexyl ester

CAS number: 27247-96-7

**US EPA TSCA public inventory**

Chemical name: Nitric acid, 2-ethylhexyl ester

CAS number: 27247-96-7

## Safety Data Sheet GAP Diesel Soot Cleaner

### Massachusetts Right To Know Components

Chemical name: Xylene (mixed isomers)  
CAS number: 1330-20-7

### New Jersey Right To Know Components

Common name: XYLENES  
CAS number: 1330-20-7

### Pennsylvania Right To Know Components

Chemical name: Benzene, dimethyl-  
CAS number: 1330-20-7

### Canadian Domestic Substances List (DSL)

Chemical name: Benzene, dimethyl-  
CAS number: 1330-20-7

### US EPA TSCA public inventory

Chemical name: XYLENES (MIXED)  
CAS number: 1330-20-7

### Massachusetts Right To Know Components

Chemical name: Ethylbenzene  
CAS number: 100-41-4

### California Proposition 65 Chemicals List

WARNING: This product can expose you to chemicals including Ethylbenzene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### New Jersey Right To Know Components

Common name: ETHYL BENZENE  
CAS number: 100-41-4

### Pennsylvania Right To Know Components

Chemical name: Benzene, ethyl-  
CAS number: 100-41-4

### Pennsylvania Right To Know Components

Chemical name: Benzene, ethyl-  
CAS number: 100-41-4

### New Jersey Right To Know Components

Common name: ETHYL BENZENE  
CAS number: 100-41-4

### Massachusetts Right To Know Components

Chemical name: Ethylbenzene  
CAS number: 100-41-4

### Canadian Domestic Substances List (DSL)

Chemical name: Benzene, ethyl-

**Safety Data Sheet**  
**GAP Diesel Soot Cleaner**

CAS number: 100-41-4

**US EPA TSCA public inventory**

Chemical name: ETHYLBENZENE

CAS number: 100-41-4

**California Prop. 65 components**

Chemical name: ETHYLBENZENE

CAS number: 100-41-4

06/11/2004 - Cancer

**US EPA TSCA public inventory**

Chemical name: Solvent naphtha (petroleum), heavy arom

CAS number: 64742-94-5

**SECTION 16: Other information**

This Safety Data Sheet was prepared in good faith from the most recent information available. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

**16.2 Preparation information**

Prepared by Craig Gourley