



## GAP PROFESSIONAL PRODUCTS

### Safety Data Sheet GAP Synthetic Power Steering Fluid - RED ATF

#### SECTION 1: Identification

##### 1.1 GHS Product identifier

|                |  |
|----------------|--|
| Product name   | GAP Synthetic Power Steering Fluid - RED ATF |
| Product number | 60975  |
| Brand          | GAP Professional Products                    |

##### 1.3 Recommended use of the chemical and restrictions on use

Synthetic Power Steering Fluid - ATF Application  
Professional Automotive, Industrial, or Commercial uses Only. Not for general consumer use.

##### 1.4 Supplier's details

|           |   |
|-----------|---|
| Name      | GAP Professional Products                           |
| Address   | 122 Route 105<br>Keswick Ridge NB E6L 1B1<br>Canada |
| Telephone | (506) 363-9708                                      |
| Fax       | (506) 363-4241                                      |
| email     | info@gapauto.com                                    |

##### 1.5 Emergency phone number

For Medical or Transport Emergencies  
CANUTEC (24 Hours)  
(613) 996-6666

#### SECTION 2: Hazard identification

##### 2.1 Classification of the substance or mixture

###### GHS classification in accordance with: WHMIS 2015

- Serious eye damage/eye irritation, Cat. 2B
- Skin corrosion/irritation, Cat. 2
- Skin sensitizer, Cat. 1

##### 2.2 GHS label elements, including precautionary statements

###### Pictograms

# Safety Data Sheet

## GAP Synthetic Power Steering Fluid - RED ATF



1. Exclamation mark

### Signal word

### Warning

### Hazard statement(s)

H320  
H315  
H317

Causes eye irritation  
Causes skin irritation  
May cause an allergic skin reaction

### Precautionary statement(s)

P202  
P280  
P308+P313  
P405  
P501  
P264  
P305+P351+P338

Do not handle until all safety precautions have been read and understood.  
Wear protective gloves/protective clothing/eye protection/face protection.  
IF exposed or concerned: Get medical advice/attention.  
Store locked up.  
Dispose of contents/container to ...  
Wash ... thoroughly after handling.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
IF ON SKIN: Wash with plenty of water/...  
Specific treatment (see ... on this label).  
If skin irritation occurs: Get medical advice/attention.  
Take off contaminated clothing and wash it before reuse.  
Avoid breathing dust/fume/gas/mist/vapors/spray.  
Contaminated work clothing should not be allowed out of the workplace.  
If skin irritation or rash occurs: Get medical advice/attention.  
Wash contaminated clothing before reuse.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

| Component  | Concentration   |
|--|-----------------|
| Distillates (petroleum), hydrotreated heavy paraffinic, if they contain > 3 % w/w DMSO extract (CAS no.: 64742-54-7; EC no.: 265-157-1; Index no.: 649-467-00-8) | < 87 % (weight) |
| CLASSIFICATIONS: Carcinogenicity, Cat. 1B. HAZARDS: H350 - May cause cancer [route].   |                 |
| PETROLEUM ADDITIVES  | < 14 % (weight) |
| CLASSIFICATIONS: No data available. HAZARDS: No data available.  |                 |
| VISCOSITY INDEX IMPROVER   | 14 % (weight)   |
| CLASSIFICATIONS: No data available. HAZARDS: No data available.  |                 |
| POLYALKYLMETHACRYLATE  | 12 % (weight)   |
| CLASSIFICATIONS: No data available. HAZARDS: No data available.  |                 |

## SECTION 4: First-aid measures

### 4.1 Description of necessary first-aid measures

## Safety Data Sheet

### GAP Synthetic Power Steering Fluid - RED ATF

|                         |  |
|-------------------------|--|
| If inhaled              | If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet, and get medical attention |
| In case of skin contact | Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician if symptoms occur. Wash contaminated clothes before reuse                          |
| In case of eye contact  | Rinse thoroughly with plenty of water for at least 15 minutes. Remove contact lenses if easy to do. Get medical attention if symptoms occur.   |
| If swallowed            | Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.  |

#### 4.2 Most important symptoms/effects, acute and delayed

Mild tissue inflammation, rash, nausea.

#### 4.3 Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1 Suitable extinguishing media

Treat surrounding material. Regular foam, Water Spray, Water Fog, carbon dioxide or dry chemical. Spray using fog nozzles. Keep containers cool with water. Use caution when applying carbon dioxide in confined spaces.

#### 5.2 Specific hazards arising from the chemical

Product is not flammable, but will burn in a fire. Product may also give rise to hazardous vapors in a fire. Vapors/fumes may be irritating, corrosive, and/or toxic.

#### 5.3 Special protective actions for fire-fighters

Wear full protective clothing and self-contained breathing apparatus

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs. See Section 8 for recommended personal protective equipment.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

LARGE SPILLS: Dike far ahead of spill to prevent further movement. Recover by pumping or by using a suitable absorbent.  
SMALL SPILLS: Contain and absorb with absorbent material and place into containers for later disposal. Wash site of spillage thoroughly with water. Dispose in suitable waste container.

#### Reference to other sections

For disposal see section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

## Safety Data Sheet

### GAP Synthetic Power Steering Fluid - RED ATF

Ensure adequate ventilation. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes and clothing. Avoid ingestion and inhalation. Avoid dust formation. dust is formed. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container(s) tightly closed. Use and store this material at room temperature away from sources of ignition, heat, direct sunlight and hot surfaces. Keep away from any incompatible materials (see section 10)

#### Specific end use(s)

Store in original container. Store as directed by manufacturer

### SECTION 8: Exposure controls/personal protection

#### 8.2 Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Showers, eyewash stations, and ventilation systems should be present and in good working order. Wash hands before breaks and at the end of workday.

#### 8.3 Individual protection measures, such as personal protective equipment (PPE)

##### Eye/face protection

Wear safety glasses with side shields (or goggles).

##### Skin protection

Wear Nitrile gloves, chemical resistant gloves.

##### Respiratory protection

Recommended: Dust mask or Respirator should be worn if product is used in confined space or used for a prolonged period of time.

### SECTION 9: Physical and chemical properties

|  |   |
|--|---|
| Appearance, such as physical state and colour    | Amber Liquid                              |
| Amber  |   |
| Amber Liquid                                     |   |
| Odour  | Characteristic                            |
| Odour threshold                                  | Not determined                            |
| pH   | N/A oil based                             |
| Melting point and freezing point                 | Not Available                             |
| Initial boiling point and boiling range          | Not Determined                            |
| Flash point                                      | 218-322°C                                 |
| Evaporation rate                                 | <1 (Butyl Acetate)                        |
| Flammability, in the case of solids and gases    | Not Determined                            |
| Upper and lower flammability or explosive limits | Not Determined                            |
| Vapour pressure                                  | <0.99 mmHg (20°C) (based on constituents) |
| Vapour density                                   | Not Determined                            |
| Relative density                                 | 0.85 (15.6°C)                             |
| Solubility                                       | Insoluble                                 |
| Partition coefficient — n-octanol/water          |   |
| Auto-ignition temperature                        | >250°C / 482°F (based on constituents)    |
| Decomposition temperature                        | Not Available                             |
| Viscosity  |   |
| <b>Additional properties</b>                     |   |
| Physical state                                   | Liquid                                    |
| Colour   | Amber                                     |
| Explosive properties                             | Not Determined                            |

**Safety Data Sheet**  
**GAP Synthetic Power Steering Fluid - RED ATF**

Oxidising properties

None

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

None under normal use conditions.

**10.2 Chemical stability**

Stable under recommended storage conditions.

**10.3 Possibility of hazardous reactions**

Stable under normal use conditions.

**10.4 Conditions to avoid**

Avoid storing in direct sunlight and avoid extremes of temperature.

**10.5 Incompatible materials**

Strong oxidizing agents

**10.6 Hazardous decomposition products**

Oxides of carbon, oxides of sulfur, oxides of phosphorus, oxides of nitrogen, amines, aliphatic compounds, toxic by-products.

**SECTION 11: Toxicological information**

**Information on toxicological effects**

**Acute toxicity**

Petroleum Distillates, Hydrotreated heavy paraffinic

Oral LD50 (rat) >5000 mg/kg

Dermal LD50 (rabbit) >5000 mg/kg

Inhalation LC50 (rat) >5.53 mg/L (4hr)

**Skin corrosion/irritation**

Petroleum Distillates, Hydrotreated heavy paraffinic - Mildly irritating to skin

**Serious eye damage/irritation**

Petroleum Distillates, Hydrotreated heavy paraffinic - Non-irritating to eyes

**Respiratory or skin sensitization**

Petroleum Distillates, Hydrotreated heavy paraffinic - Not dermally sensitizing

**Germ cell mutagenicity**

Petroleum Distillates, Hydrotreated heavy paraffinic - Not mutagenic

**Carcinogenicity**

Petroleum Distillates, Hydrotreated heavy paraffinic - Carcinogenic potential is reduced for highly refined distillates. Tumors have developed in animal studies, but were dependent on the concentration of impurities. Not classified as to carcinogenicity to humans.

**Reproductive toxicity**

Petroleum Distillates, Hydrotreated heavy paraffinic - Reproductive performance and offspring development were not adversely affected in mice and rats (1000 mg/kg)

**Specific target organ toxicity (STOT) - single exposure**

Petroleum Distillates, Hydrotreated heavy paraffinic - N/D

**Specific target organ toxicity (STOT) - repeated exposure**

## Safety Data Sheet

### GAP Synthetic Power Steering Fluid - RED ATF

Petroleum Distillates, Hydrotreated heavy paraffinic - In a 13 week oral study in rats at up to 500mg/kg/day, the LOAEL was 125 mg/kg/day based on organ weight changes, reddening/discoloration of organs and atrophy in male sex organs.

#### Aspiration hazard

This product does not pose an appreciable aspiration hazard.

#### Additional information

None

### SECTION 12: Ecological information

#### Toxicity

ENVIRONMENTAL DATA: No known significant effects or critical hazards

ECOTOXICOLOGICAL INFORMATION: Not Available

#### Persistence and degradability

Petroleum Distillates, Hydrotreated heavy paraffinic - Not inherently biodegradable

#### Bioaccumulative potential

Petroleum Distillates, Hydrotreated heavy paraffinic - May contain constituents with the potential to bioaccumulate.

#### Other adverse effects

None

### SECTION 13: Disposal considerations

#### Disposal methods

##### Product disposal

Dispose of accordance in local, and provincial regulations for solvent and oil materials

##### Packaging disposal

Disposal should be in accordance with applicable regional, national and local laws and regulations.

##### Other disposal recommendations

Prevent the material from entering drains and water courses. Do not discharge directly to a water source. Advise Authorities if spillage has entered watercourse or sewer or has contaminated soil or vegetation.

### SECTION 14: Transport information

#### DOT (US)

Not dangerous goods

#### IMDG

Not dangerous goods

#### IATA

Not dangerous goods

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations specific for the product in question

##### Canadian Domestic Substances List (DSL)

All components of this product are listed on the Canadian Domestic Substance List

**Safety Data Sheet**  
**GAP Synthetic Power Steering Fluid - RED ATF**

Canadian Non-Domestic Substances List (NDSL)

**SECTION 16: Other information**

**16.2 Preparation information**  
Prepared by Craig Gourley