



GAP PROFESSIONAL PRODUCTS

Safety Data Sheet GAP Prof. Squeal Free Brake Treatment

SECTION 1: Identification

1.1 GHS Product identifier

Product name	GAP Prof. Squeal Free Brake Treatment
Product number	70103
Brand	GAP Professional Products

1.3 Recommended use of the chemical and restrictions on use

Squeal Free Brake Treatment
Professional Automotive, Industrial, or Commercial uses Only. Not for general consumer use.

1.4 Supplier's details

Name	GAP Professional Products
Address	122 Route 105 Keswick Ridge NB E6L 1B1 Canada
Telephone	(506) 363-9708
Fax	(506) 363-4241
email	info@gapauto.com

1.5 Emergency phone number

For Medical or Transport Emergencies
CANUTEC (24 Hours)
(613) 996-6666

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

GHS classification in accordance with: WHMIS 2015

- Serious eye damage/eye irritation, Cat. 2B
- Skin corrosion/irritation, Cat. 2
- Skin sensitizer, Cat. 1
- Carcinogenicity, Cat. 1B
- Acute toxicity, inhalation, Cat. 5
- Acute toxicity, oral, Cat. 5
- Carcinogenicity, Cat. 2
- Serious eye damage/eye irritation, Cat. 2

Safety Data Sheet

GAP Prof. Squeal Free Brake Treatment

2.2 GHS label elements, including precautionary statements

Pictograms



1. Exclamation mark; 2. Health hazard; 3. Corrosion

Signal word

Danger

Hazard statement(s)

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H320	Causes eye irritation
H350	May cause cancer [route]
H351	Suspected of causing cancer [route]

Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash ... thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water/...
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see ... on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P501	Dispose of contents/container to ...

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Component	Concentration
3-methylhexane (CAS no.: 589-34-4; EC no.: 209-643-3)	10 - 20 % (weight)
CLASSIFICATIONS: No data available. HAZARDS: No data available.	
2-methylhexane (CAS no.: 591-76-4; EC no.: 209-730-6)	10 - 20 % (weight)
CLASSIFICATIONS: No data available. HAZARDS: No data available.	
Heptane (CAS no.: 142-82-5; EC no.: 205-563-8; Index no.: 601-008-00-2)	10 - 20 % (weight)
CLASSIFICATIONS: Flammable liquids, Cat. 2; Aspiration hazard, Cat. 1; Skin corrosion/irritation, Cat. 2; Specific target organ toxicity, single exposure, Cat. 3; Hazardous to the aquatic environment, short-term (acute), Cat. 1; Hazardous to the aquatic environment, long-term (chronic), Cat. 1. HAZARDS: H225 - Highly flammable liquid and vapor; H304 - May be fatal if swallowed and enters airways; H315 - Causes skin irritation; H336 - May cause drowsiness or dizziness; H400 - Very toxic to aquatic life; H410 - Very toxic to aquatic life with long lasting effects.	
Isopropanol (CAS no.: 67-63-0; EC no.: 200-661-7; Index no.: 607-403-00-6)	10 - 20 % (weight)

Safety Data Sheet

GAP Prof. Squeal Free Brake Treatment

CLASSIFICATIONS: Flammable liquids, Cat. 2; Eye damage/irritation, Cat. 2A; Specific target organ toxicity, single exposure, Cat. 3; Specific target organ toxicity, repeated exposure, Cat. 2; Eye damage/irritation, Cat. 1; Hazardous to the aquatic environment, short-term (acute), Cat. 1; Hazardous to the aquatic environment, long-term (chronic), Cat. 1. HAZARDS: H225 - Highly flammable liquid and vapor; H318 - Causes serious eye damage; H319 - Causes serious eye irritation; H335 - May cause respiratory irritation; H336 - May cause drowsiness or dizziness; H373 - May cause damage to organs [organs] through prolonged or repeated exposure [route]; H400 - Very toxic to aquatic life; H410 - Very toxic to aquatic life with long lasting effects.	
GRAPHITE powder (CAS no.: 7782-42-5; EC no.: 231-955-3)	5 - 15 % (weight)
CLASSIFICATIONS: No data available. HAZARDS: No data available.	
2-methylpentane (CAS no.: 107-83-5; EC no.: 203-523-4)	2 - 10 % (weight)
CLASSIFICATIONS: No data available. HAZARDS: No data available.	
3-methylpentane (CAS no.: 96-14-0; EC no.: 202-481-4)	2 - 10 % (weight)
CLASSIFICATIONS: No data available. HAZARDS: No data available.	
N-HEXANE (CAS no.: 110-54-3; EC no.: 203-777-6; Index no.: 601-037-00-0)	2 - 8 % (weight)
CLASSIFICATIONS: Flammable liquids, Cat. 2; Reproductive toxicity, Cat. 2; Aspiration hazard, Cat. 1; Specific target organ toxicity, single exposure, Cat. 3; Specific target organ toxicity, repeated exposure, Cat. 2; Skin corrosion/irritation, Cat. 2; Hazardous to the aquatic environment, long-term (chronic), Cat. 2. HAZARDS: H225 - Highly flammable liquid and vapor; H304 - May be fatal if swallowed and enters airways; H315 - Causes skin irritation; H336 - May cause drowsiness or dizziness; H361f - ; H373 - May cause damage to organs [organs] through prolonged or repeated exposure [route]; H411 - Toxic to aquatic life with long lasting effects. [SCLs/M-factors/ATEs]: STOT RE 2; H373: C ≥ 5 %	
Bentonite (< 2% crystalline silica) (CAS no.: 1302-78-9; EC no.: 215-288-5)	1 - 5 % (weight)
CLASSIFICATIONS: No data available. HAZARDS: No data available.	
n-Butyl alcohol (CAS no.: 71-36-3; EC no.: 200-751-6; Index no.: 603-004-00-6)	1 - 5 % (weight)
CLASSIFICATIONS: Flammable liquids, Cat. 3; Acute toxicity, oral, Cat. 4; Specific target organ toxicity, single exposure, Cat. 3; Skin corrosion/irritation, Cat. 2; Eye damage/irritation, Cat. 1. HAZARDS: H226 - Flammable liquid and vapor; H302 - Harmful if swallowed; H315 - Causes skin irritation; H318 - Causes serious eye damage; H335 - May cause respiratory irritation; H336 - May cause drowsiness or dizziness.	
PROPYLENE GLYCOL MONOMETHYL ETHER (CAS no.: 107-98-2; EC no.: 203-539-1; Index no.: 603-064-00-3)	1 - 5 % (weight)
CLASSIFICATIONS: Flammable liquids, Cat. 3; Specific target organ toxicity, single exposure, Cat. 3. HAZARDS: H226 - Flammable liquid and vapor; H336 - May cause drowsiness or dizziness.	
Distillates (petroleum), steam-cracked, polyimd (CAS no.: 68131-77-1)	1 - 5 % (weight)
CLASSIFICATIONS: No data available. HAZARDS: No data available.	

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

If inhaled	If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet, and get medical attention
In case of skin contact	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician if symptoms occur. Wash contaminated clothes before reuse
In case of eye contact	Rinse thoroughly with plenty of water for at least 15 minutes. Remove contact lenses if easy to do. Get medical attention if symptoms occur.
If swallowed	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms/effects, acute and delayed

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

4.3 Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically. Symptoms may be delayed.

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Treat surrounding material. Regular foam, Water Spray, Water Fog, carbon dioxide or dry chemical. Spray using fog nozzles. Keep containers cool with water. Use caution when applying carbon dioxide in confined spaces. Do not use a solid water stream as it may scatter or spread fire.

Safety Data Sheet

GAP Prof. Squeal Free Brake Treatment

5.2 Specific hazards arising from the chemical

Development of hazardous combustion gases or vapor possible in the event of fire. May cause expansion or decompose explosively when heated or involved in fire.

5.3 Special protective actions for fire-fighters

As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear. Fight fire from a safe distance, with adequate cover.

Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs. See Section 8 for recommended personal protective equipment.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

LARGE SPILLS: Dike far ahead of spill to prevent further movement. Recover by pumping or by using a suitable absorbent.

SMALL SPILLS: Contain and absorb with absorbent material and place into containers for later disposal. Wash site of spillage thoroughly with water. Dispose in suitable waste container.

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure adequate ventilation. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes and clothing. Avoid ingestion and inhalation. Avoid dust formation. dust is formed. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container(s) tightly closed. Use and store this material at room temperature away from sources of ignition, heat, direct sunlight and hot surfaces. Keep away from any incompatible materials (see section 10)

Specific end use(s)

Store in original container. Store as directed by manufacturer

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. Heptane (CAS: 142-82-5 EC: 205-563-8)

IOELV-LTEL (Inhalation): 2085 mg/m³; EU (EU/OSHA)

List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-LTEL (Inhalation): 500 ppm; EU (EU/OSHA)

List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

PEL [Heptane (n-Heptane)] (Inhalation): 500 ppm; US (US/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL [Heptane (n-Heptane)] (Inhalation): 2000 mg/m³; US (US/OSHA)

Safety Data Sheet

GAP Prof. Squeal Free Brake Treatment

OSHA Annotated Table Z-1, www.osha.gov

PEL [Heptane (n-Heptane)] (Inhalation): 400 ppm, (ST) 500 ppm; US (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL [Heptane (n-Heptane)] (Inhalation): 85 ppm, (ST) 440 ppm [15-min]; US (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

2. Isopropanol (CAS: 67-63-0)

PEL [Isopropyl alcohol] (Inhalation): 400 ppm; US (US/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL [Isopropyl alcohol] (Inhalation): 980 mg/m³; US (US/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL [Isopropyl alcohol] (Inhalation): 400 ppm, (ST) 500 ppm; US (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL [Isopropyl alcohol] (Inhalation): 400 ppm, (ST) 500 ppm; US (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

3. n-Hexane (CAS: 110-54-3 EC: 203-777-6)

IOELV-LTEL (Inhalation): 72 mg/m³; EU (EU/OSHA)

List no. 2 under Council Directive 98/24/EC as amended. List last updated on 8/25/2023.

IOELV-LTEL (Inhalation): 20 ppm; EU (EU/OSHA)

List no. 2 under Council Directive 98/24/EC as amended. List last updated on 8/25/2023.

PEL (Inhalation): 500 ppm; US (US/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 1800 mg/m³; US (US/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 50 ppm; US (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 50 ppm; US (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

4. n-Butyl alcohol (CAS: 71-36-3)

TLV[®] (Inhalation): 20 ppm (ACGIH)

PEL (Inhalation): 100 ppm; US (US/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 300 mg/m³; US (US/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): (C) 50 ppm; US (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): (C) 50 ppm; US (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

5. PROPYLENE GLYCOL MONOMETHYL ETHER (CAS: 107-98-2 EC: 203-539-1)

IOELV-LTEL [1-methoxypropan-2-ol] (Inhalation): 375 mg/m³; EU (EU/OSHA)

Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-LTEL [1-methoxypropan-2-ol] (Inhalation): 100 ppm; EU (EU/OSHA)

Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-STEL [1-methoxypropan-2-ol] (Inhalation): 568 mg/m³; EU (EU/OSHA)

Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-STEL [1-methoxypropan-2-ol] (Inhalation): 150 ppm; EU (EU/OSHA)

Safety Data Sheet

GAP Prof. Squeal Free Brake Treatment

Skin designation: Yes. List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

8.2 Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Showers, eyewash stations, and ventilation systems should be present and in good working order. Wash hands before breaks and at the end of workday.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Wear Nitrile gloves, chemical resistant gloves.

Body protection

Eye Protection - Must wear appropriate anti-corrosion goggles.

Hand protection - Must wear acid and alkali resistant chemical protective gloves.

Respiratory protection - Must wear appropriate personal respiratory protective equipment.

Skin and body protection - Recommended to wear acid and alkali resistant chemical protective clothing.

Respiratory protection

Dust mask or Respirator should be worn if product is used in confined space or used for a prolonged period of time.

SECTION 9: Physical and chemical properties

Appearance, such as physical state and colour	Black Liquid
Odour	Low odour
Odour threshold	N/D
pH	N/A
Melting point and freezing point	N/D
Initial boiling point and boiling range	N/D
Flash point	N/D
Evaporation rate	<1 (Butyl Acetate)
Flammability, in the case of solids and gases	N/D
Upper and lower flammability or explosive limits	N/D
Vapour pressure	N/D
Vapour density	Not Determined
Relative density	0.7968
Solubility	Insoluble
Partition coefficient — n-octanol/water	N/D
Auto-ignition temperature	N/D
Decomposition temperature	Not Available
Viscosity	N/D
Additional properties	
Physical state	Liquid
Colour	Black
Explosive properties	N/D
Oxidising properties	None

SECTION 10: Stability and reactivity

10.1 Reactivity

Contact with incompatible substances can cause decomposition or other chemical reactions.

10.2 Chemical stability

Stable under recommended storage conditions.

Safety Data Sheet

GAP Prof. Squeal Free Brake Treatment

10.3 Possibility of hazardous reactions

Stable under normal use conditions.

10.4 Conditions to avoid

Avoid storing in direct sunlight and avoid extremes of temperature.

10.5 Incompatible materials

Oxidants and halogen. Oxidants, alkali metals, alkaline earth metals and aluminum. Metal acetylide, halogen, interhalogen, halogen oxides, nitric acid, nitrous oxide, nitrates, nitrites, halogen oxyacid salts, chromates, permanganates, inorganic peroxides, metal oxides and peroxyformic acid.

10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

N-hexane 25000mg/kg(Rat) No information available 169.188mg/L(Rat)

Heptane No information available No information available 103mg/L(Rat)

Butan-1-ol 790mg/kg(Rat) 3400mg/kg(Rabbit) 24.252mg/L(Rat)

1-methoxypropan-2-ol 11700mg/kg(Mouse) 13000mg/kg(Rabbit) No information available

Propan-2-ol 5045mg/kg(Rat) 12800mg/kg(Rabbit) No information available

Skin corrosion/irritation

Causes skin irritation(Category 2)

Serious eye damage/irritation

Causes serious eye damage(Category 1)

Respiratory or skin sensitization

Skin sensitization Based on available data, the classification criteria are not met

Respiratory sensitization Based on available data, the classification criteria are not met

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

Suspected of damaging fertility or the unborn child(Category 2)

Specific target organ toxicity (STOT) - single exposure

STOT-single exposure May cause drowsiness or dizziness(Category 3(drowsiness or dizziness))

Specific target organ toxicity (STOT) - repeated exposure

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure(Category)

Aspiration hazard

Safety Data Sheet

GAP Prof. Squeal Free Brake Treatment

May be fatal if swallowed and enters airways(Category 1)

SECTION 12: Ecological information

Toxicity

Acute aquatic toxicity

N-hexane - LC50: 57.8mg/L (96h)(Fish)

Heptane - LC50: 375mg/L (96h)(Fish)

Graphite LC50: 100mg/L (96h)(Fish)

Butan-1-ol - LC50: 1910mg/L (96h)(Fish) EC50: 1980mg/L (48h)(Crustaceans) ErC50: >1000mg/L (72h)(Algae)

1-methoxypropan-2-ol - LC50: 6812mg/L (96h)(Fish)

Propan-2-ol - LC50: 9640mg/L (96h)(Fish) EC50: >1000mg/L (48h)(Crustaceans) ErC50: >1000mg/L (72h)(Algae)

Bentonite - LC50: 19000mg/L (96h)(Fish)

Chronic aquatic toxicity

Butan-1-ol - NOEC: 4.1mg/L(Crustaceans) NOEC: 180mg/L(Algae)

Propan-2-ol - NOEC: >100mg/L(Crustaceans) NOEC: 1000mg/L(Algae)

Persistence and degradability

3-methylhexane - Low

2-Methylhexane - Low

Heptane - Low

Graphite - Low

2-methylpentane - Low

3-methylpentane - Low

N-hexane - Low

Butan-1-ol Low(Half-life = 54 days) Low(Half-life = 3.65 days)

1-methoxypropan-2-ol Low(Half-life = 56 days) Low(Half-life = 1.7 days)

Bioaccumulative potential

3-methylhexane Low Log Kow=3.7056

2-Methylhexane Low Log Kow=3.7056

Heptane High Log Kow=4.66

Graphite Low Log Kow=0.5294

2-methylpentane Low Log Kow=3.2145

3-methylpentane Low Log Kow=3.6

N-hexane Medium Log Kow=3.9

Butan-1-ol Low BCF=64

1-methoxypropan-2-ol Low BCF=2

Mobility in soil

3-methylhexane Low 241.3

2-Methylhexane Low 230.3

Heptane Low 274.7

Graphite Low 23.74

2-methylpentane Low 124.9

3-methylpentane Low 130.8

N-hexane Low 149

Butan-1-ol Medium 2.443

1-methoxypropan-2-ol High 1

Safety Data Sheet

GAP Prof. Squeal Free Brake Treatment

Results of PBT and vPvB assessment

3-methylhexane Insufficient information, temporarily unable to evaluate
2-Methylhexane Insufficient information, temporarily unable to evaluate
Heptane Insufficient information, temporarily unable to evaluate
Propan-2-ol Not PBT/vPvB
Graphite Not applicable
2-methylpentane Insufficient information, temporarily unable to evaluate
3-methylpentane Insufficient information, temporarily unable to evaluate
N-hexane Not PBT/vPvB
Bentonite Insufficient information, temporarily unable to evaluate
Butan-1-ol Not PBT/vPvB
1-methoxypropan-2-ol Not PBT/vPvB
Petroleum Hydrocarbon
Resin
Insufficient information, temporarily unable to evaluate

Other adverse effects

None

SECTION 13: Disposal considerations

Disposal methods

Product disposal

Dispose of accordance in local, and provincial regulations for solvent and oil materials

Packaging disposal

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Other disposal recommendations

Prevent the material from entering drains and water courses. Do not discharge directly to a water source. Advise Authorities if spillage has entered watercourse or sewer or has contaminated soil or vegetation.

SECTION 14: Transport information

DOT (US)

UN Number: 3082

Class:

Packing Group: III

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Reportable quantity (RQ): 5000(N-hexane) ; 5000(Butan-1-ol)

Marine pollutant:

Poison inhalation hazard:

IMDG

UN Number:

Class:

Packing Group:

EMS Number:

Proper Shipping Name:

IATA

UN Number:

Class:

Packing Group:

Safety Data Sheet
GAP Prof. Squeal Free Brake Treatment

Proper Shipping Name:

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Canadian Domestic Substances List (DSL)

All components of this product are listed on the Canadian Domestic Substance List

Canadian Domestic Substances List (DSL)

Chemical name: Hexane, 2-methyl-

CAS number: 591-76-4

Canadian Domestic Substances List (DSL)

Chemical name: Heptane

CAS number: 142-82-5

Canadian Domestic Substances List (DSL)

Chemical name: 2-Propanol

CAS number: 67-63-0

Canadian Domestic Substances List (DSL)

Chemical name: Graphite

CAS number: 7782-42-5

Canadian Domestic Substances List (DSL)

Chemical name: Pentane, 2-methyl-

CAS number: 107-83-5

Canadian Domestic Substances List (DSL)

Chemical name: Pentane, 3-methyl-

CAS number: 96-14-0

Canadian Domestic Substances List (DSL)

Chemical name: Hexane

CAS number: 110-54-3

Canadian Domestic Substances List (DSL)

Chemical name: Aluminatesilicate

CAS number: 1327-36-2

Canadian Domestic Substances List (DSL)

Chemical name: Bentonite

CAS number: 1302-78-9

Canadian Domestic Substances List (DSL)

Chemical name: Kaolin

CAS number: 1332-58-7

Canadian Domestic Substances List (DSL)

Chemical name: Montmorillonite ((Al_{1.33}-1.67Mg_{0.33}-0.67)(Ca₀-1Na₀-1)_{0.33}Si₄(OH)₂O₁₀.xH₂O)

Safety Data Sheet
GAP Prof. Squeal Free Brake Treatment

CAS number: 1318-93-0

Canadian Domestic Substances List (DSL)

Chemical name: 1-Butanol

CAS number: 71-36-3

Canadian Domestic Substances List (DSL)

Chemical name: 2-Propanol, 1-methoxy-

CAS number: 107-98-2

Canadian Domestic Substances List (DSL)

Chemical name: Distillates (petroleum), steam-cracked, polymd.

CAS number: 68131-77-1

Canadian Non-Domestic Substances List (NDSL)

Canadian Non-Domestic Substances List (NDSL)

Chemical name: Hexane, 3-methyl-

CAS number: 589-34-4

SECTION 16: Other information

This Safety Data Sheet was prepared in good faith from the most recent information available. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

16.2 Preparation information

Prepared by Craig Gourley